

ELPARTS



herthundbuss.com

Highlights



Passt immer!

 **HERTH+BUSS**

“Real-life” implemented improvement process

We, the management are committed to the TQM concept, because we value the trust our customers place in us and want to maintain it in the long term.

We see our relationship with our customers as a partnership which must be constantly improved. As a result, we continuously check even established processes for opportunities for improvement.

And not because anyone is forcing us to do so, because we have met the criteria for the ISO certification for a long time.

Instead, we are motivated by the chance to achieve even better results in our work together and to help our customers to increase their competitiveness and hence secure their long-term success.

That is what we call a “real-life implemented improvement process”, and it is also what our many long-term customers especially appreciate about their cooperation with Herth+Buss.



We are certified according to:

- ISO 9001:2015 Quality management
- VDA 6.2 Quality management
- StVZO Verification



Content



Installation

4 - 47

1

Tools

48 - 75

2

Electrics

76 - 81

3

Lighting

82 - 89

4





Installation

Adapter, fuse	40
Assortment, cable ties	10
Assortment, fasteners	7
Assortment, hose connectors	43
Assortment, plug housings	32
Assortment, repair cable	16
Assortment, spacer	44
Base Plate, trailer hitch	20
Battery Post Clamp	25 - 26
Cable Connector Kit	11
Cable Repair Set, air flow meter	13 - 14
Cable Repair Set, EGR valve	14
Cable Repair Set, air flow meter	
Cable Repair Set, tail light	13 - 14
Charge Cable, electric vehicle	27
Connector Cable, camshaft sensor	15
Corrugated Pipe	29
Electric Cable	8 - 10
Fuel Hose	28
Fuse	33 - 34
Fuse Holder	38 - 40
Fuse Kit	35 - 37
Jumper Cables	24 - 25
Plug	19 - 21
Plug Connector	21 - 23
Plug Housing Set	30 - 31
Repair set, negative pressure line	42
Repair set, pressure line	43
Repair Set, wash water line	41
Screw	26
Socket	18 - 22
Socket Adapter	19 - 27
Wall Mounting, cable spool	10
Wall Mounting, fuel lines	28

» ATTACHMENT PARTS







Effortless fixing!

There are different clips for many areas on the vehicle which secure the connection between the body and paneling, for example on paneling in the boot, in the vehicle's interior, such as the door paneling, in the engine bay, clips for sidebars etc. The product group Attachment parts offers an extensive range, which includes clips, blind rivets,

retaining clips, expanding rivets, screws and other fixing parts. We also offer various assortments. Depending on the equipment variant, these contain up to 240 parts and fit vehicles from BMW, Mercedes-Benz, VAG, Ford or Vauxhall (Opel).

Dimension specifications

The dimensions of our body fasteners are specified for the width, height and depth, diameter and pitch circle diameter, amongst other things. This is shown in the catalogue as follows.





Assortment, fasteners

Version: VAG
Mercedes-Benz



	Quantity	DU	Article no.
	185	1	54267001
Content		QU	
Assortment Box		1	99994507
Blind Rivet		10	50267064
Clip		10	50267047
		10	50267050
		10	50267059
		10	50267060
		10	50267062
		10	50267066
Expanding Rivet		20	50267014
		10	50267038
Grommet		10	50267026
Holding Bracket		10	50267044
		10	50267069
		25	50267140
Screw		10	50267057
		10	50267065
		10	50267067
Accessories	see	DU	
Frame, assortment box HandyBox	Katalog04	1	99994532
Mounting Wedge	Page 51	1	95926000

Assortment, fasteners

Version: VAG
BMW
Opel
Peugeot
Mercedes-Benz



	Quantity	DU	Article no.	
	240	1	54267002	
Content		QU		
Assortment Box		1	99994507	
Clip		10	50267007	
		10	50267037	
		10	50267048	
		10	50267081	
		10	50267083	
		10	50267084	
		10	50267086	
		10	50267087	
		10	50267088	
		10	50267143	
		10	50267145	
		10	50267148	
	Expanding Rivet		10	50267001
			20	50267017
		10	50267038	
		10	50267041	
		10	50267042	
		10	50267080	
		10	50267082	
		10	50267085	
		10	50267144	
		10	50267146	
		10	50267147	
Accessories	see	DU		
Frame, assortment box HandyBox	Katalog04	1	99994532	
Mounting Wedge	Page 51	1	95926000	



FLY Electric Cable

Material: PVC
Temperature range: -40 to +70 °C
DIN / ISO: 6722



Conductor Number conductor	Packing Type	Wire cross section mm ²	Cable Core Colour	QU	DU	Article no.		
1	Coil	1 x 0,75	●	Metre	100	51274206000		
			●	Metre	100	51274206005		
		1 x 1,0	●	Metre	100	51274207000		
			●	Metre	100	51274207005		
		1 x 1,5	●	Metre	100	51274208005		
			●	Metre	100	51274208000		
		1 x 2,5	●	Metre	50	51274209000		
			●	Metre	50	51274209005		
		1 x 4,0	●	Metre	25	51274210000		
			●	Metre	25	51274210005		
		Accessories				see	DU	
		Wall Mounting, cable spool				Page 10	1	51274200

FLYY Electric Cable

Shape: Flat
Material: PVC
Temperature range: -40 to +70 °C
DIN / ISO: 6722



Conductor Number conductor	Wire cross section mm ²	Packing Type	Cable Core Colour	Colour	QU	DU	Article no.
2	2 x 1,5	Coil	● ●	●	Metre	25	51274248000
Accessories					see	DU	
Wall Mounting, cable spool					Page 10	1	51274200

XYFAZ Electric Cable

Material: PVC
Temperature range: -40 to +70 °C
DIN / ISO: 6722



Conductor Number conductor	Wire cross section mm ²	Packing Type	Cable Core Colour	QU	DU	Article no.
2	2 x 0,75	Coil	● ●	Metre	50	51274227
Accessories				see	DU	
Wall Mounting, cable spool				Page 10	1	51274200



Electric Cable

Material: Silicone
Surface: Tin-plated
Temperature range: -40 to +180 °C



Extremely flexible electric cable with very fine diameter of the individual copper strands and highly elastic silicone insulation. Also in use in the Herth+Buss RepCab.

Conductor Number conductor	Length m	Packing Type	Wire cross section mm ²	Cable Core Colour	DU	Article no.
1	5	Blister Pack	1 x 0,5	●	1	51275505000
				●	1	51275505002
				●	1	51275505005
			1 x 0,75	●	1	51275506000
				●	1	51275506002
				●	1	51275506005
			1 x 1,5	●	1	51275508002
				●	1	51275508005
			1 x 2,5	●	1	51275509000
				●	1	51275509005
			1 x 4,0	●	1	51275510000
				●	1	51275510005

FLRYY

Electric Cable



Cable ID: FLRYY
Material: PVC
Temperature range: -40 to +70 °C
DIN / ISO: 6722

Conductor Number conductor	Wire cross section mm ²	Packing Type	Cable Core Colour	QU	DU	Article no.
8	7 x 1,0	Ring	● ● ● ● ● ● ● ●	Metre	50	51275608000
	1 x 1,5		○			

FLYY

Electric Cable

Cable ID: FLYY
Material: PVC
Temperature range: -40 to +70 °C
DIN / ISO: 6722



Packing Type	Conductor Number conductor	Wire cross section mm ²	Cable Core Colour	Colour	QU	DU	Article no.
Ring	2	2 x 1,5	● ●	● ●	Metre	50	51275348000
		2 x 2,5	● ●	● ●	Metre	50	51275349000
	7	7 x 1,5	● ● ● ● ● ● ●	● ●	Metre	50	51275378000



FLRY-A

Electric Cable

Material: PVC
Temperature range: -40 to +105 °C
DIN / ISO: 6722



Wall Mounting, cable spool



Conductor Number conductor	Packing Type	Wire cross section mm ²	Cable Core Colour	QU	DU	Article no.
1	Coil	1 x 0,22	●	Metre	100	51274903000
		1 x 0,35	●	Metre	100	51274904000
		1 x 0,5	●	Metre	100	51274905002
			●	Metre	100	51274905000
Accessories				see	DU	
Wall Mounting, cable spool				Page 10	1	51274200

An empty cable wall mount with body fasteners for up to five coils.

WxHxD: 616 x 150 x 155 mm

	DU	Article no.
	1	51274200

Assortment, cable ties


Material: Polyamid 6.6
Temperature range: -40 to +85 °C
Inspection Tag: UL94 V2



	Quantity	DU	Article no.
	700	1	50266070
Content	Colour	QU	
CableTie	●	100	50266001
	●	100	50266002
	●	100	50266003
	●	100	50266004
	●	100	50266490
	●	100	50266491
	●	100	50266492
Accessories		see	DU
CableTie Pliers		Katalog08	1 90942365



Cable Connector Kit



Design: Sealed Version **Info:** with gel filling
Corrosion resistant

Plug Type	Quantity	DU	Article no.		
T-Union	 30	1	 50252595066		
Content	Number of Poles terminal	Cable-Ø mm	Colour	QU	
Cable Connector	2	to 1,5		10	50252590
	3	to 1,7		10	50252591
	3	to 3,8		10	50252592



» REPAIR KIT OVERVIEW



Alternator



Mass air flow meter



Wheel speed sensor



Lambda sensor



Windscreen wiper motor



Parking sensor



Side marker light



Headlights



Injector valve




EGR valve



Interior heating fan



Combination rearlight





RepCon

Cable Repair Set, tail light



Number of Poles: 4 terminal **Info:** with socket housing
Temperature range: -25 to +140 °C with pipe

Cable Length mm	Cable Cross Section mm ²	Manufacturer Restriction	Version	Connector	DU	Article no.
175	1	Alfa Romeo Fiat	147 Punto Punto Evo Grande Punto		1	51277254
Accessories				see	DU	
Squeeze Connector Crimpsal II				Katalog04	50	50252552

RepCon

Cable Repair Set, tail light



Number of Poles: 5 terminal **Info:** with socket housing
Temperature range: -25 to +140 °C with pipe

Cable Length mm	Cable Cross Section mm ²	Manufacturer Restriction	Version	Connector	DU	Article no.
175	1	Fiat	Panda Panda Van Punto Punto Van Stilo Stilo Multi Wagon		1	51277277
Accessories				see	DU	
Squeeze Connector Crimpsal II				Katalog04	50	50252552

RepCon

Cable Repair Set, tail light



Number of Poles: 6 terminal **Info:** with socket housing
Temperature range: -25 to +140 °C with pipe

Cable Length mm	Cable Cross Section mm ²	Manufacturer Restriction	Connector	DU	Article no.	
175	1	Citroen Fiat Peugeot		1	51277255	
Accessories				see	DU	
Squeeze Connector Crimpsal II				Katalog04	50	50252552

RepCon

Cable Repair Set, air flow meter



Number of Poles: 6 terminal **Info:** with socket housing
Temperature range: -25 to +140 °C with seal
with pipe

Cable Length mm	Cable Cross Section mm ²	Manufacturer Restriction	Connector	DU	Article no.	
175	0,5	Citroen Fiat Peugeot		1	51277253	
Accessories				see	DU	
Squeeze Connector Crimpsal II				Katalog04	50	50252552



RepCon

Cable Repair Set, tail light



Number of Poles: 6 terminal **Info:** with socket housing
Temperature range: -25 to +140 °C with pipe

Cable Length mm	Cable Cross Section mm ²	Manufacturer Restriction	Connector	DU	Article no.
250	0,75 to 1	Fiat Lada Dacia Citroen Peugeot Renault		1	51277261
Accessories			see	DU	
Squeeze Connector Crimpsal II			Katalog04	50	50252552

RepCon

Cable Repair Set, EGR valve Cable Repair Set, air flow meter



Number of Poles: 6 terminal **Info:** with socket housing
Temperature range: -25 to +140 °C with pipe

Cable Length mm	Cable Cross Section mm ²	Manufacturer Restriction	Connector	DU	Article no.
200	0,5	Nissan Opel Renault	 NEW	1	51277317
Accessories			see	DU	
Squeeze Connector Crimpsal II			Katalog04	50	50252552

RepCon

Cable Repair Set, air flow meter



Number of Poles: 5 terminal **Info:** with gaskets/seals
Temperature range: -25 to +140 °C with socket housing
with pipe

Cable Length mm	Cable Cross Section mm ²	Manufacturer Restriction	Connector	DU	Article no.
200	0,75	Alfa Romeo Citroen Fiat Lancia Nissan Opel Peugeot Suzuki Volvo	 NEW	1	51277288
Accessories			see	DU	
Squeeze Connector Crimpsal II			Katalog04	50	50252552

RepCon

Cable Repair Set, tail light



Number of Poles: 7 terminal **Info:** with socket housing
Temperature range: -25 to +140 °C with pipe

Cable Length mm	Cable Cross Section mm ²	Manufacturer Restriction	Version	Connector	DU	Article no.
200	1	Mercedes-Benz	C-class CLC-class CLS E-class GLK-class S-class	 NEW	1	51277289
Accessories			see	DU		
Squeeze Connector Crimpsal II			Katalog04	50	50252552	



Connector Cable, camshaft sensor



Oil leaking from the camshaft sensor plug is a familiar problem on Mercedes-Benz petrol engines. The fault is design-related and cannot be rectified in the long term by replacing the sensor. Due to the capillary effect, the oil can infiltrate the harness to reach the control unit and eventually cause electronic failure and damage to individual parts. Such damage can be prevented with the Herth+Buss oil-stop cable. Fine copper sleeves have been incorporated into both lines of the oil-stop cable in order to prevent the oil from spreading. These have

subsequently also been wrapped in heat-shrink tubing. We recommend installing one oil-stop cable on every M111 (engine code), two on every M271 and as many as four on every M272 (V6).

How long does it take to fit the oil-stop cable? Fitting it will take a maximum of five minutes. Detach the harness from the sensor before inserting the oil-stop cable from Herth+Buss between the connection on the sensor and the old harness.



Number of Poles: 2 terminal
Temperature range: -25 to +125 °C

Info: with gaskets/seals
with cable ties
with copper casing
with protection hose

Cable Length mm	Cable Cross Section mm ²	Manufacturer Restriction	Connector	DU	Article no.
110	1	Mercedes-Benz		1	51277300






RepLine

Assortment, repair cable

Info: with gaskets/seals
with shrink squeeze connector



Cable Length mm	Manufacturer Restriction	DU	Article no.
300	BMW Mercedes-Benz Opel VAG	1	54277001
Content	Diameter mm	Colour	QU
Assortment Box			1 99994523
Foam Insert, assortment box			1 99994540
Repair Cable RepLine (AMPTyco JPT AMPTyco MCP 2,8)			5 51277220
Repair Cable RepLine (AMPTyco JPT)			5 51277203
			5 51277216
Repair Cable RepLine (AMPTyco MCON 1,2)			5 51277228
Repair Cable RepLine (AMPTyco MCP 1,5)			5 51277214
			5 51277215
Repair Cable RepLine (AMPTyco MCP 2,8)			5 51277217
Repair Cable RepLine (AMPTyco MCP 6,3)			5 51277221
Repair Cable RepLine (AMPTyco MQS)			5 51277207
			5 51277211
Repair Cable RepLine (AMPTyco MT II AMPTyco MCP 1,5)			5 51277213
Repair Cable RepLine (AMPTyco MT II)			5 51277209
Repair Cable RepLine (AMPTyco SPT AMPTyco MCP 6,3 AMP Tyco MCP 4,8)			5 51277225
Repair Cable RepLine (AMPTyco SPT)			5 51277223
Repair Cable RepLine (Delphi Ducon 0,8 F)			5 51277201
Sealing-/Protection Plugs ELA (AMP Tyco ELA 3,6)	3,9	●	50 50282039
Sealing-/Protection Plugs ELA (AMP Tyco ELA 4)	4,7	●	50 50282085
Sealing-/Protection Plugs ELA (AMP Tyco ELA 5,2)	5,5 to 5,8	●	50 50282081
Sealing-/Protection Plugs ELA (AMP Tyco ELA 5,4)	5,9 to 6,3	●	50 50282058
Sealing-/Protection Plugs ELA (AMP Tyco ELA 7,2)	7,9 to 8,2	○	50 50282044
Squeeze Connector Crimpseal II		●	75 50252552
Universal Container		○	6 99994524
		○	1 99994534
Accessories	see	DU	
Crimping Pliers Insert	Katalog08	1	95942187
	Katalog08	1	95942347
Crimping Pliers CrimPro 10	Page 53	1	95942330
	Page 53	1	95942331
Crimping Pliers CrimPro 30	Page 54	1	95942164
	Page 54	1	95942166
Frame, assortment box HandyBox	Katalog04	1	99994532
Gas Soldering Torch Burner	Page 66	1	95921001
Hot Air Dryer HeatGun	Page 66	1	95920000



» APPLICATION EXAMPLE



Connecting the cables



The key benefit of our Replines is that the contacts are already optimally crimped with the silicone lead. This means that the user does not have to carry out the crimping process.



The repair line merely has to be connected with the cable in the vehicle (shown here in yellow). Both cables must be stripped beforehand (e.g. with our stripper).



A crimp, shrink or soldered shrink connector can be used for the connection.



The cables are then crimped with the connector one after the other. In this example with our crimping pliers CrimPro10, alternatively with CrimPro30.



The connectors are then shrunk with a hot air fan.



Socket



Number of Poles: 13 terminal
Trailer Hitch: with rear fog light deactivation
Mounting Type: Screw Connection
Material: Plastic
Shape: Flat
Info: with seal
 Outflow middle

Voltage V	Capacity at 12V	Overall Height mm	DIN / ISO	DU	Article no.
12	16 A (1,5 mm ²) 25 A (2,5 mm ²)	45	11446	1	51305031
Content				QU	
Seal, trailer socket				1	51305170

Socket



Tight seal on both sides of the contact areas thanks to moulded contacts, an additional insulator and individually sealed conductors. This thereby prevents the infiltration of water into the cable harness by way of the contacts, thus preventing any time- and cost-intensive damage that occurs as a result. The front section of the socket remains replaceable in its entirety, however. If the cover is torn off, or if the socket body is externally damaged, the housing can be replaced quickly and simply.

Number of Poles: 13 terminal
Plug Type: Crimp Contact
Material: GRP (Glass fibre Reinforced Plastic)
Contact surface: Copper-tin-(zinc) electrolyte
IP-Code: IP 69K
Info: with gaskets/seals with contacts
 Outflow middle
 Outflow left

Voltage V	Capacity at 12V	DIN / ISO			DU	Article no.
12	16 A (1,5 mm ²) 25 A (2,5 mm ²)	11446			1	51305037
Content		DIN / ISO	Cross section mm ²	Number of Poles terminal	Diameter mm	QU
Crimp Connector RK 2,5 (TE Connectivity)			1 to 2,5		2,5	13
Housing		11446		13		1
Sealing-/Protection Plugs ELA (AMPTyco ELA 5,4)			1 to 2,5		5,9 to 6,3	13
Accessories				Cross section mm ²	see	DU
Crimping Pliers Insert				0,5 to 1 1,5 to 2,5	Katalog08	1
Crimping Pliers CrimPro 10					Page 53	1

Socket



The second micro-switch can be used universally. This is often used to switch off the Park Distance Control (PDC).

Number of Poles: 13 terminal
Trailer Hitch: with rear fog light deactivation
Mounting Type: Screw Connection
Material: Plastic
Contact surface: Copper-tin-(zinc) electrolyte
Shape: Flat
Info: with two micro switches with seal
 Outflow middle
Combi Switch Function: Directional Contact

Voltage V	Capacity at 12V	DIN / ISO	DU	Article no.
12	16 A (1,5 mm ²) 25 A (2,5 mm ²)	11446	1	51305036
Content			QU	
Seal, trailer socket			1	51305170



Socket



Socket can be fully integrated and flexibly positioned, with new fastening points for mounting in or on the swan-neck towbar or fixing panel. The double contact system combines with the single-conductor seals to make it im-

possible for moisture to penetrate into the vehicle electrical system even launching a sports boat into the water will pose no problems (water-tight to a depth of 1 m).

Number of Poles: 13 terminal
Plug Type: Crimp Contact
Material: Polyamid 6.6

Contact surface: Copper-tin-(zinc) electrolyte
IP-Code: IP X9K
Info: with contacts with gaskets/seals Side Connector



Voltage V	Capacity at 12V	DIN / ISO	DU	Article no.	
12	16 A (1,5 mm ²) 25 A (2,5 mm ²)	11446	1	51305038	
Content	Cross section mm ²	Diameter mm	Colour	QU	
Crimp Connector RK 2,5 (TE Connectivity)	0,5 to 1	2,5		8	50251867
	1 to 2,5	2,5		6	50251868
Sealing-/Protection Plugs ELA (AMP Tyco ELA 5,4)	0,35 to 1	5,9 to 6,3		8	50282057
	1 to 2,5	5,9 to 6,3		6	50282058
Sealing-/Protection Plugs ELB (AMP Tyco ELB 5,2)		5,4 to 5,6		5	50282043

Plug

Number of Poles: 13 terminal
Mounting Type: Screw Connection Bayonet
Terminal/Clamp: with cable gland
Material: Plastic
Info: with seal with strain relief



Voltage V	Capacity at 12V	Cable-Ø mm	DIN / ISO	DU	Article no.
12	16 A (1,5 mm ²) 25 A (2,5 mm ²)	11,4 to 14	11446	1	51305630
Accessories			see	DU	
Sealing-/Protection Plugs			Katalog04	1	50281030
			Katalog04	1	50281049

Socket Adapter

Trailer Hitch: from 13 to 7 pin
Material: Plastic
Length: 52 mm



Voltage V	Capacity at 12V	DIN / ISO	DU	Article no.
12	16 A (1,5 mm ²) 25 A (2,5 mm ²)	11446 1724 N-Typ	1	51305472



Base Plate, trailer hitch

This trailer hitch base plate is suitable for making an extension lead.



Number of Poles: 7 terminal
13 terminal
Material: Plastic
Info: with screws

Voltage V	DU	Article no.
12	1	51305025



Socket



The USB connection's very high charging current of 3000 mA ensures reliable charging of electronic devices such as smartphones, mobile phones, navigation devices, digital cameras and even tablets. Can be mounted with or without bolted-on plate.

Terminal/Clamp: with USB socket
Cable Length: 150 mm
Info: with overvoltage protection with bolted-on plate with screws
Electromagnetic Compatability (EMC) with lid
Output Voltage USB: 5 V
Output current USB: 3000 mA



Voltage V	Fitted Diameter mm	DU	Article no.
12 to 24	27,8	1	51306862

Socket



The USB connection's very high charging current of 3000 mA ensures reliable charging of electronic devices such as smartphones, mobile phones, navigation devices, digital cameras and even tablets.

Terminal/Clamp: with USB socket
Material: ABS (Acrylonitrile-Butadiene-Styrene Copolymerisate)
Fitting Position: Body
Cable Length: 1000 mm
Info: with overvoltage protection with screws
Output Voltage USB: 5 V
Output current USB: 3000 mA
WxHxD: 34 x 15,25 x 42 mm



Voltage V	DU	Article no.
12 to 24	1	51306863



Socket



The USB connection's very high charging current of 3000 mA ensures reliable charging of electronic devices such as smartphones, mobile phones, navigation devices, digital cameras and even tablets.

Terminal/Clamp:	with USB socket	Output Voltage USB:	5 V
Material:	PC (Polycarbonate)	Output current USB:	3000 mA
Fitting Position:	Body	WxHxD:	95 x 33 x 85 mm
Info:	with overvoltage protection with screws Electromagnetic Compatability (EMC) with screws		

Voltage V	Rated current A	Inner diameter mm	DIN / ISO	DU	Article no.
12 to 24	16	20,95	SAE	1	51306864

Plug Connector



Material: PVC **Info:** with buckle protection

Length mm	Cable-Ø mm	DU	Article no.
30	4	10	50281006

for article number 51306060, 51306063, 51306061, 51306147, 51306132, 51306132099, 51306142, 51306125

» **MAGCODE POWER SYSTEM**



The MagCode Power System is ideally suited to cars, lorries, motorbikes, mobile homes and boats. It is currently used for the external load maintenance of the Maybach, Bentley and Mercedes AMG gullwing and convertible cars. It is also included as a series option with the new Mercedes Actros.

12/24 V



**MagCode Power System Pro
Plug**

Mounting Type: Screw Connection
IP-Code: IP 42
Temperature range: to +70 °C

Rated current A	Wire cross section mm ²	Voltage V	DU	Article no.
to 25	2,5	12	1	51306108
		24	1	51306111



**MagCode Power System Pro
Socket**

Mounting Type: Pre-assembled
IP-Code: IP 5K9K
Temperature range: to +70 °C

Rated current A	Fitted Diameter mm	Fitting Depth mm	Voltage V	DU	Article no.
to 25	28	16,5	12	1	51306107
			24	1	51306110
Accessories			see	DU	
Cover, power socket MagCode			Katalog04	1	51306057





MagCode Power System Pro Plug Connector

Mounting Type: Screw Connection Pre-assembled Info: with socket with plug



Voltage V	Rated current A	DU	Article no.
12	to 25	1	51306106
Content		Wire cross section mm ²	QU
Plug MagCode Power System Pro		2,5	1
Socket MagCode Power System Pro			1
Accessories		see	DU
Cover, power socket MagCode		Katalog04	1
			51306057

www.herthundbuss.com/channel

MagCode Power System Pro Plug Connector

Mounting Type: Screw Connection Pre-assembled Info: with socket with plug



Voltage V	Rated current A	DU	Article no.
24	to 25	1	51306109
Content		Wire cross section mm ²	QU
Plug MagCode Power System Pro		2,5	1
Socket MagCode Power System Pro			1
Accessories		see	DU
Cover, power socket MagCode		Katalog04	1
			51306057

www.herthundbuss.com/channel



» JUMPER CABLES



The right design for every requirement and every use:
We recommend the jumper cables carstart and truckstart as a professional tool for everyday use. The carboost and truckboost cables are indispensable starting aids in any vehicle. The bikestart starting aid system is the right solution for motorcycle riders. All cables are supplied in robust bags to protect them.



carstart safe
Jumper Cables



This jumper cable is made of CCA conductor material (copper coated aluminium), which offers the same conductance as a copper cable with a cross-section of 25 mm². The professional pliers made from steel plate are reinforced

with cast iron inserts.

Cross section:
Material:
for petrol engines to capacity:

25 mm²
CCA (Copper Coated Aluminium)
5500 cc

for diesel engines from capacity:
Info:

3000 cc
with steel plate pliers
with cast iron insert
with earth strap
with overvoltage protection
with storage bag

Voltage V	Rated current A	Design	Length m	DU	Article no.
12 to 24	to 350	Insulated	4	1	52289865

carstart safe
Jumper Cables



Cross section:
Material:
for petrol engines to capacity:

25 mm²
Copper
5500 cc

for diesel engines from capacity:
Info:

3000 cc
with steel plate pliers
with cast iron insert
with overvoltage protection
with storage bag

Voltage V	Rated current A	Design	Length m	DU	Article no.
12 to 24	to 350	Insulated	3,5	1	52289765



carboost safe
Jumper Cables



Cross section: 25 mm² **for diesel engines from capacity:** 3000 cc
Material: CCA (Copper Coated Aluminium) **Info:** with plastic pliers with overvoltage protection with storage bag
for petrol engines to capacity: 5500 cc

Voltage V	Rated current A	Design	DIN / ISO	Length m	DU	Article no.
12 to 24	to 350	Insulated	72553	3,5	1	52289950

carboost safe
Jumper Cables



Cross section: 35 mm² **for diesel engines from capacity:** 4000 cc
Material: CCA (Copper Coated Aluminium) **Info:** with plastic pliers with overvoltage protection with storage bag
for petrol engines to capacity: 7000 cc

Voltage V	Rated current A	Design	DIN / ISO	Length m	DU	Article no.
12 to 24	to 480	Insulated	72553	4,5	1	52289953

Battery Post Clamp



Number of Poles: 1 terminal
Battery Clamp Version: Terminal Screw Pressed Part
Terminal post screw: single-sided mounting
Material: Brass
Surface: Tin-plated
Info: with bolts

Battery Pole Diameter mm	Clamp	Thread Length mm	Thread Size	DU	Article no.
17,5	+	28,5	M8	5	52285034
Content			Thread Size	QU	
Screw			M8 x 28	1	52285520
Accessories		Rated current A	see	DU	
Cover, battery post clamp			Katalog04	10	50281115
Fuse CF		50	Katalog04	1	50295880
		75	Katalog04	1	50295881
		100	Katalog04	1	50295882
		125	Katalog04	1	50295883
		150	Katalog04	1	50295884
		175	Katalog04	1	50295885
		200	Katalog04	1	50295886
Screw		250	Katalog04	1	50295887
		300	Katalog04	1	50295888
			Page 26	5	52285560





Battery Post Clamp



Cross section: to 70 mm² **Surface:** Zinc-coated
Battery Clamp Version: Terminal Screw **Version:** Renault, Peugeot
Material: Steel
 Plastic

Battery Pole Diameter mm	Clamp	Thread Size	Colour	DU	Article no.
17,5	+	M8		1	52285191

Battery Post Clamp



Cross section: to 70 mm² **Surface:** Zinc-coated
Battery Clamp Version: Terminal Screw **Version:** Renault, Peugeot
Material: Steel
 Plastic

Battery Pole Diameter mm	Clamp	Thread Size	Colour	DU	Article no.
15,9	-	M8		1	52285192

Screw



Battery Clamp Version: with auxiliary port **Info:** with nut

Thread Size	DU	Article no.
M8 x 30	5	52285560
Accessories	see	DU
Cable Connector	Katalog04	100
		50251566





NRGkick 32A

Charge Cable, electric vehicle



The NRGkick 32 A charging unit is more than just a Wallbox. NRGkick expands the options for charging your electric vehicle far beyond public charging stations. Electricity is available almost everywhere; NRGkick makes it accessible for your electric car with a charging capacity of up to 22 kW. With NRGkick, the Wallbox migrates from the wall of your home into the charger cable itself. Thanks to the adapter set available as an accessory, you can enjoy unrestricted flexibility and charge anywhere quickly.

- option of setting the charging current easily and directly using a push-button on the NRGkick
- integrated residual-current-protection mechanism (AC 30 mA, DC 6 mA) for direct and alternating residual currents, for your

safety

- automatic detection of NRGkick adapters, PE conductor testing through loop-impedance measurement, switching contact diagnosis
- protected against theft and tampering
- extremely compact dimensions
- verified by TÜV Technical Inspection Association and CE-compliant
- with energy measurement module and Bluetooth
- Use the free NRGkick app to view charging data (performance, energy, voltage, current, charging costs and range) and control the charging station.
- adjustment of the charging current also possible while charging and in increments of 1 A between 6 A and 32 A

Version:

Bluetooth

Info:

Electromagnetic

Temperature range:

-30 to +50 °C

Compatibility (EMC))

DIN / ISO	Cable Length m	IP-Code	DU	Article no.
IEC/EN 62752 IEC/EN 62196-1 IEC/EN 60309-2	5	IP 66	1	95960101
Accessories		see	DU	
Socket Adapter NRGkick 32A/32A light		Page 27	1	95960170

NRGkick 32A light

Charge Cable, electric vehicle



The NRGkick 32 A light charging unit is more than just a Wallbox. NRGkick expands the options for charging your electric vehicle far beyond public charging stations. Electricity is available almost everywhere; NRGkick makes it accessible for your electric car with a charging capacity of up to 22 kW. With NRGkick, the Wallbox migrates from the wall of your home into the charger cable itself. Thanks to the adapter set available as an accessory, you can enjoy unrestricted flexibility and charge anywhere quickly.

- option of setting the charging current easily and directly using a push-button on the

NRGkick

- integrated residual-current-protection mechanism (AC 30 mA, DC 6 mA) for direct and alternating residual currents, for your safety
- automatic detection of NRGkick adapters, PE conductor testing through loop-impedance measurement, switching contact diagnosis
- protected against theft and tampering
- extremely compact dimensions
- verified by TÜV Technical Inspection Association and CE-compliant

Temperature range:

-30 to +50 °C

Info:

Electromagnetic
Compatibility (EMC))

DIN / ISO	Cable Length m	IP-Code	DU	Article no.
IEC/EN 62752 IEC/EN 62196-1 IEC/EN 60309-2	5	IP 66	1	95960102
Accessories		see	DU	
Socket Adapter NRGkick 32A/32A light		Page 27	1	95960170

NRGkick 32A/32A light

Socket Adapter



With the adapter set for the NRGkick 32 A and NRGkick 32 A light, it is possible to charge an electric vehicle at any conventional power socket. All adapters feature a detection function and an original EV charger cable. Contents:

- adapter, CEE 32 A to CEE 16 A, max. 11 kW
- adapter, CEE 32 A to CEE 16 A blue, max. 3.7 kW
- adapter, CEE 32 A to Schuko, max. 13 A

	DU	Article no.
	1	95960170
for article number		
95960101, 95960102		



Fuel Hose

Material: NBR (nitrile butadiene rubber)
Rubber with textile reinforcement
Polychloroprene (Neoprene)

Temperature range: -35 to +110 °C

DIN / ISO: 73379-2A

Operating Pressure: 10 bar

Burst Pressure: 30 bar

Info: not suitable for biodiesel



Fuel hoses made from a rubber top layer and textile inlay for conveying petrol (also E10) and diesel (not biodiesel). Resistant to oil, heat, ozone and the effects of the weather.

Packing Type	Wall thickness mm	Outer Diameter mm	Inner diameter mm	Bending radius mm	QU	DU	Article no.
Coil	2,65	8,5	3,2	30	Metre	15	51280032
	3	10,5	4,5	35	Metre	15	51280045
		12	6	60	Metre	15	51280060
		13,5	7,5	75	Metre	10	51280075
		15,5	9,5	70	Metre	10	51280095
	3,5	19	12	80	Metre	5	51280120
Accessories					see	DU	
Wall Mounting, fuel lines					Page 28	1	51280660

Wall Mounting, fuel lines

WxHxD: 500 x 750 x 120 mm



Multiple mult	Colour	DU	Article no.
6	○	1	51280660



Co-flex Corrugated Pipe

Design: Two-piece

Material: Polyamid 6

Temperature range: -40 to +150 °C

Inspection Tag: UL94 V2

Chemical Properties: FMVSS 302
UV resistant
Solvent resistant
Oil resistant
with marten protection

Info:


Packing Type: Ring

Ideal for follow-up installation and repairs.
Areas of application:

- automotive industry
- ship and train construction
- mechanical engineering

- switching cabinets
- heating and air-conditioning technology
- electrical industry
- computers, hifi

Wall thick- ness mm	Nominal Size mm	Outer Dia- meter mm	Inner dia- meter mm	Bending ra- dius mm	QU	DU	Article no.
0,1	6	10	6,3	30	Metre	50	51271106
0,15	10	13,5	8,8	55	Metre	50	51271110
0,2	14	18,7	13,2	75	Metre	50	51271114
0,3	20	25,7	20,2	105	Metre	50	51271120
	23	31,3	23,9	125	Metre	50	51271123
	37	43,2	32,5	170	Metre	25	51271137





Plug Housing Set

Number of Poles: 2 terminal
Version: Neutral
suitable for: VAG



Plug Type	Socket Width mm	IP-Code	DU	Article no.
Blade Terminal Sleeve	1,5	IP X7	1	50390652
Content	Number of Poles terminal	Cross section mm ²	QU	
Crimp Connector MT II (TE Connectivity)		0,2 to 0,5	3	50251901
		0,5 to 1	3	50251902
Plug Housing	2		1	50390670
Sealing-/Protection Plugs ELA (AMP Tyco ELA 3,6)		0,35 to 0,5	2	50282038
		0,5 to 0,75	2	50282040
Accessories	Cross section mm ²	see	DU	
Crimping Pliers Insert (AMPTyco MT I AMP Tyco MT II AMP Tyco JPT)	0,2 to 0,35 0,5 to 1 1,5 to 2,5	Katalog08	1	95942345
Crimping Pliers CrimPro 10		Page 53	1	95942330
		Page 53	1	95942331
Release Tool, flat-/round plug (AMPTyco MT I AMP Tyco MT II)		Katalog08	1	95945336
Release tool, housing (VAG FEP Opel Fiat)		Page 51	1	95945445

Plug Housing Set

Number of Poles: 2 terminal
Version: Neutral
suitable for: VAG
MERCEDES-BENZ



Plug Type	Socket Width mm	IP-Code	DU	Article no.
Blade Terminal Sleeve	2,8	IP X7	1	50390653
Content	Number of Poles terminal	Cross section mm ²	QU	
Crimp Connector JPT (TE Connectivity)		0,5 to 1	3	50251899
Plug Housing	2		1	50390662
Sealing-/Protection Plugs ELA (AMP Tyco ELA 5,2)		0,5 to 1,5	2	50282081
Accessories	Cross section mm ²	see	DU	
Crimping Pliers Insert (AMPTyco JPT ELA)	0,35 0,5 to 1 1,5 to 2,5	Katalog08	1	95942193
Crimping Pliers CrimPro 30		Page 54	1	95942164
		Page 54	1	95942166
Release Tool, flat-/round plug (AMPTyco JPT AMP Tyco JT AMP Tyco SPT AMP Tyco ST)		Katalog08	1	95945335
Release tool, housing (VAG FEP Opel Fiat)		Page 51	1	95945445
for article number				
82710380, 82710249				

Plug Housing Set

Number of Poles: 3 terminal
Version: Neutral
suitable for: VAG



Plug Type	Socket Width mm	IP-Code	DU	Article no.
Blade Terminal Sleeve	1,5	IP X7	1	50390654
Content	Number of Poles terminal	Cross section mm ²	QU	
Crimp Connector MT II (TE Connectivity)		0,5 to 1	4	50251902
Plug Housing	3		1	50390664
Sealing-/Protection Plugs ELA (AMP Tyco ELA 3,6)		0,5 to 0,75	3	50282040
Sealing-/Protection Plugs ELB (AMP Tyco ELB 3,6)			2	50282041
Accessories	Cross section mm ²	see	DU	
Crimping Pliers Insert (AMPTyco MT I AMP Tyco MT II AMP Tyco JPT)	0,2 to 0,35 0,5 to 1 1,5 to 2,5	Katalog08	1	95942345
Crimping Pliers CrimPro 10		Page 53	1	95942330
		Page 53	1	95942331
Release Tool, flat-/round plug (AMPTyco MT I AMP Tyco MT II)		Katalog08	1	95945336
Release tool, housing (VAG FEP Opel Fiat)		Page 51	1	95945445



Plug Housing Set

Number of Poles:
Version:
suitable for:

4 terminal
Neutral
VAG



Plug Type	Socket Width mm	IP-Code	DU	Article no.
Blade Terminal Sleeve	1,5	IP X7	1	50390655
Content	Number of Poles terminal	Cross section mm ²	QU	
Crimp Connector MT II (TE Connectivity)		0,5 to 1	5	50251902
Plug Housing	4		1	50390666
Sealing-/Protection Plugs ELA (AMPTyco ELA 3,6)		0,5 to 0,75	4	50282040
Sealing-/Protection Plugs ELB (AMPTyco ELB 3,6)			3	50282041
Accessories	Cross section mm ²	see	DU	
Crimping Pliers Insert (AMPTyco MT I AMP Tyco MT II AMP Tyco JPT)	0,2 to 0,35 0,5 to 1 1,5 to 2,5	Katalog08	1	95942345
Crimping Pliers CrimPro 10		Page 53	1	95942330
		Page 53	1	95942331
Release Tool, flat-/round plug (AMPTyco MT I AMP Tyco MT II)		Katalog08	1	95945336
Release tool, housing (VAG FEP Opel Fiat)		Page 51	1	95945445

Plug Housing Set

Number of Poles:
Version:
suitable for:

4 terminal
Neutral
VAG



Plug Type	Socket Width mm	IP-Code	DU	Article no.
Blade Terminal Sleeve	2,8	IP X7	1	50390656
Content	Number of Poles terminal	Cross section mm ²	QU	
Crimp Connector JPT (TE Connectivity)		0,5 to 1	5	50251899
Plug Housing	4		1	50390690
Sealing-/Protection Plugs ELA (AMPTyco ELA 5,2)		0,5 to 1,5	4	50282081
Sealing-/Protection Plugs ELB (AMPTyco ELB 5,2)			3	50282043
Accessories	Cross section mm ²	see	DU	
Crimping Pliers Insert (AMPTyco JPT ELA)	0,35 0,5 to 1 1,5 to 2,5	Katalog08	1	95942193
Crimping Pliers CrimPro 30		Page 54	1	95942164
		Page 54	1	95942166
Release Tool, flat-/round plug (AMPTyco JPT AMP Tyco JT AMP Tyco SPT AMP Tyco ST)		Katalog08	1	95945335
Release tool, housing (VAG FEP Opel Fiat)		Page 51	1	95945445



Assortment, plug housings

Version:
suitable for:

Neutral
VAG



The plug housings for connecting flat plugs or blade receptacles in sizes 1.5 and 2.8 mm facilitate electrical connection between the cable harnesses and a variety of electronic components. A safety slider which works in both directions (even for designs with two rows) is integrated into the housing. Through simple and safe handling, this allows the secondary lock of the contacts to be realised and thereby also

guarantees the safety of the electrical contacting. It is only possible to connect the plug if the secondary lock is active. The plug housings can be used in all areas of a vehicle (engine bay, interior, areas exposed to splash water etc.). With these housings (in a neutral version), we offer a reliable coupling connection for vehicle construction.

IP-Code		Quantity	DU	Article no.
IP X7		558	1	54290200
Content	Number of Poles terminal	Cross section mm ²	QU	
Assortment Box			1	99994522
Crimp Connector JPT (TE Connectivity)		0,5 to 1	50	50251899
Crimp Connector JPT MCP 2,8 (TE Connectivity)		0,5 to 1	50	50251896
Crimp Connector MCP 1,5 MT II (TE Connectivity)		0,5 to 1	50	50251468
Crimp Connector MT II (TE Connectivity)		0,5 to 1	50	50251902
Plug Housing	2		10	50390662
	2		10	50390663
	2		10	50390670
	2		10	50390671
	4		3	50390666
	4		3	50390667
	4		3	50390690
	4		3	50390691
	6		1	50390672
	6		1	50390673
	6		1	50390674
	6		1	50390675
	8		1	50390660
8		1	50390661	
Sealing-/Protection Plugs ELA (AMPTyco ELA 3,6)		0,5 to 0,75	100	50282040
Sealing-/Protection Plugs ELA (AMPTyco ELA 5,2)		0,5 to 1,5	100	50282081
Sealing-/Protection Plugs ELB (AMPTyco ELB 3,6)			50	50282041
Sealing-/Protection Plugs ELB (AMPTyco ELB 5,2)			50	50282043
Accessories	Cross section mm ²	see	DU	
Crimping Pliers Insert (AMPTyco JPT ELA)	0,35 0,5 to 1 1,5 to 2,5	Katalog08	1	95942193
Crimping Pliers Insert (AMPTyco MT I AMP Tyco MT II AMP Tyco JPT)	0,2 to 0,35 0,5 to 1 1,5 to 2,5	Katalog08	1	95942345
Crimping Pliers CrimPro 10		Page 53	1	95942330
		Page 53	1	95942331
Crimping Pliers CrimPro 30		Page 54	1	95942164
		Page 54	1	95942166
Frame, assortment box HandyBox		Katalog04	1	99994532
Release Tool, flat-/round plug (AMPTyco JPT AMP Tyco JT AMP Tyco SPT AMP Tyco ST)		Katalog08	1	95945335
Release Tool, flat-/round plug (AMPTyco MT I AMP Tyco MT II)		Katalog08	1	95945336
Release Tool, flat-/round plug (AMPTyco MT II)		Katalog08	1	95945370
Release tool, housing (VAG FEP Opel Fiat)		Page 51	1	95945445



MICRO2

Fuse

Fuse type:
Material:
Surface:
WxHxD:

Micro blade fuse
Nylon
Silver-plated
9,1 x 15,3 x 3,8 mm



The MICRO2 fuse fulfils all the demands asked of a modern vehicle fuse. The small size means that multiple circuits can be fused in even the tightest of spaces. Very small dimensions combined with the high temperature resis-

tance required for tough ambient conditions make the MICRO2 fuse particularly recommendable.

Voltage V	Rated current A	Colour	DU	Article no.
to 32	5		5	50295645
	7,5		5	50295646
	10		5	50295647
	15		5	50295648
	20		5	50295649
	25		5	50295650
	30		5	50295651
Accessories		see	DU	
Fuse Tester		Katalog08	1	90945340



www.herthandbuss.com/channel

MICRO3

Fuse

Fuse type:
Material:
Surface:
WxHxD:

Micro blade fuse
Nylon
Silver-plated
14,4 x 18,1 x 4,2 mm



The MICRO3 fuse has three contacts, with two fuse elements sharing a common central contact. The small size means that multiple circuits can be fused in even the tightest of spaces. Very small dimensions combined with

the high temperature resistance required for tough ambient conditions make the MICRO3 fuse particularly recommendable.

Voltage V	Rated current A	Colour	DU	Article no.
to 32	5		5	50295665
	7,5		5	50295666
	10		5	50295667
	15		5	50295668
Accessories		see	DU	
Fuse Tester		Katalog08	1	90945340




www.herthandbuss.com/channel



MULTI6

Fuse

Fuse type: Multi Plug-in Fuses
Material: PSU (Polysulfone)
WxHxD: 40 x 28,2 x 5 mm



One multi flat-type plug-in fuse with one in-feed and six outlets. This allows six circuits to be fused in the smallest possible space. The multi flat-type plug-in fuse is used in various models from Mercedes-Benz.

Voltage V	Rated current A	Colour	DU	Article no.
to 32	5		1	50295162
	7,5		1	50295163



MCASE

Fuse

Fuse type: Block Fuse
DIN / ISO: 8820-4
JASO D612
Shape: Slitted
WxHxD: 9,7 x 17,5 x 6,2 mm



Voltage V	Rated current A	Colour	DU	Article no.
to 32	20		1	50295353
	25		1	50295354
	30		1	50295355
	40		1	50295356
	50		1	50295357
	60		1	50295358





ATO Fuse Kit

Fuse type: Standard Flat Fuse
DIN / ISO: 72581/3C
SAE J 1284
8820-3
JASO D612
WxHxD: 19,05 x 18,54 x 5 mm



The ATO fuse is the standard fuse for vehicle circuits. The rated power is shown via the colour coding. Features include a three-part structure with copper contacts, low voltage drop and high reliability in harsh ambient con-

ditions. The transparent material means that burnt-out fuses can be identified easily.

Voltage V	Rated current A	Quantity	DU	Article no.	
to 32	5 to 30	7	1	50296477066	
Content	Fuse type	Rated current A	Colour	QU	Article no.
Fuse ATO	Standard Flat Fuse	5		1	50295405
	Standard Flat Fuse	7,5		1	50295407
	Standard Flat Fuse	10		1	50295410
	Standard Flat Fuse	15		1	50295415
	Standard Flat Fuse	20		1	50295420
	Standard Flat Fuse	25		1	50295425
	Standard Flat Fuse	30		1	50295430
Accessories			see	DU	Article no.
Fuse Tester			Katalog08	1	90945340

MINI Fuse Kit

Fuse type: Mini-Flat Fuse
DIN / ISO: 72581/3F
8820-3
JASO D612
SAE J2077
Surface: Silver-plated
WxHxD: 10,9 x 16,3 x 3,8 mm



The mini flat-type plug-in fuse is quickly becoming the new standard for circuit protection in vehicles. Its miniature design enables more circuits to be protected with an overall low space requirement. Very small dimensions

combined with the high temperature resistance required for tough ambient conditions make the mini fuse particularly recommendable.

Voltage V	Rated current A	Quantity	DU	Article no.	
to 32	5 to 30	7	1	50296577066	
Content	Fuse type	Rated current A	Colour	QU	Article no.
Fuse MINI	Mini-Flat Fuse	5		1	50295775
	Mini-Flat Fuse	7,5		1	50295776
	Mini-Flat Fuse	10		1	50295777
	Mini-Flat Fuse	15		1	50295778
	Mini-Flat Fuse	20		1	50295779
	Mini-Flat Fuse	25		1	50295780
	Mini-Flat Fuse	30		1	50295781



Low Profile MINI

Fuse Kit

Fuse type: Low profile mini blade fuse
WxHxD: 10,9 x 9 x 3,8 mm



Low-profile mini fuses offer similar performance characteristics to standard mini fuses. Their low height saves space and weight. They are designed for open cable lugs/bifurcated contacts, so that there is no need for contact sleeves

and thus enabling weight and material savings when designing fuse boxes.

Voltage V	Rated current A	Quantity	DU	Article no.	
to 58	2 to 30	14	1	50296797066	
Content	Fuse type	Rated current A	Colour	QU	Article no.
Fuse Low Profile MINI	Low profile mini blade fuse	2	●	1	50295790
	Low profile mini blade fuse	3	●	1	50295791
	Low profile mini blade fuse	4	●	1	50295792
	Low profile mini blade fuse	5	●	1	50295793
	Low profile mini blade fuse	7,5	●	2	50295794
	Low profile mini blade fuse	10	●	2	50295795
	Low profile mini blade fuse	15	●	2	50295796
	Low profile mini blade fuse	20	●	2	50295797
	Low profile mini blade fuse	25	○	1	50295798
	Low profile mini blade fuse	30	●	1	50295799

MICRO2

Fuse Kit

Fuse type: Micro blade fuse
Surface: Silver-plated
WxHxD: 9,1 x 15,3 x 3,8 mm



Voltage V	Rated current A	Quantity	DU	Article no.	
to 32	5 to 30	7	1	50296647066	
Content	Fuse type	Rated current A	Colour	QU	Article no.
Fuse MICRO2	Micro blade fuse	5	●	1	50295645
	Micro blade fuse	7,5	●	1	50295646
	Micro blade fuse	10	●	1	50295647
	Micro blade fuse	15	●	1	50295648
	Micro blade fuse	20	●	1	50295649
	Micro blade fuse	25	○	1	50295650
	Micro blade fuse	30	●	1	50295651
Accessories	see		DU		
Fuse Tester	Katalog08		1	90945340	



MICRO3

Fuse Kit

Fuse type: Micro blade fuse
Surface: Silver-plated
WxHxD: 14,4 x 18,1 x 4,2 mm



Voltage V	Rated current A	Quantity	DU	Article no.	
to 32	5 to 15	4	1	50296667066	
Content	Fuse type	Rated current A	Colour	QU	
Fuse MICRO3	Micro blade fuse	5		1	50295665
	Micro blade fuse	7,5		1	50295666
	Micro blade fuse	10		1	50295667
	Micro blade fuse	15		1	50295668
Accessories			see	DU	
Fuse Tester			Katalog08	1	90945340



MINI Fuse Holder

Fuse type: for mini-blade plug-in fuse
DIN / ISO: 72581/3F
Info: connectable in series




The 4-fold fuse holder can be installed in line and can also be combined with a relay socket. This enables little power distributors to be created quickly and easily.

Voltage V	Rated current A	Cross section mm ²	DU	Article no.		
to 32	to 30	0,5 to 2,5	1	50390444		
Accessories		Number of Poles terminal	Cross section mm ²	see	DU	
Crimp Connector JPT (TE Connectivity)			0,5 to 1	Katalog04	50	50251826
				Katalog04	50	50253316
		1 to 2,5	Katalog04	50	50251871	
Protective Cap, fuse holder				Katalog04	1	50390444034
Relay Socket		5		Katalog04	1	50390903



MINI Fuse Holder

Fuse type: for mini-blade plug-in fuse
DIN / ISO: 72581/3F
Info: with gaskets/seals connectable in series with connecting cable



Voltage V	Rated current A	Cross section mm ²	DU	Article no.	
to 32	to 30	2,5	1	50390902	
Accessories			see	DU	
Protective Cap, fuse holder			Katalog04	10	50390902034

MICRO2 Fuse Holder

Fuse type: for micro blade fuse
Info: with connecting cable



Voltage V	Rated current A	Cross section mm ²	DU	Article no.
to 32	to 30	3,3	1	50390657



MICRO3 Fuse Holder


Fuse type: for micro blade fuse
Info: with connection line with gaskets/seals



Voltage V	Rated current A	DU	Article no.
to 32	to 15	 1	50390715
Accessories		see	DU
Protective Cap, fuse holder		Katalog04	10
			50390715034

ATO Fuse Holder

Fuse type: for standard plug-in fuse
Material: Polyamid 6.6
DIN / ISO: 72581/3C
Surface: Tin-plated
Info: with connecting cable




Additional loads can be connected quickly and easily using the junction bracket. The fuse previously hidden in the fuse box is removed and replaced by the additional bracket. The fuse is then placed in the bottom connection point of

the bracket in order to re-establish protection of the electrical circuit. The top connection point should be fitted with an additional fuse to protect the newly connected load.

Voltage V	Rated current A	Cross section mm ²	Cable Length mm	DU	Article no.
to 32	to 15	1,3	120	1	50390431

MINI Fuse Holder

Fuse type: for mini-blade plug-in fuse
Material: Polyamid 6.6
DIN / ISO: 72581/3F
Surface: Tin-plated
Info: with connecting cable



Additional loads can be connected quickly and easily using the junction bracket. The fuse previously hidden in the fuse box is removed and replaced by the additional bracket. The fuse is then placed in the bottom connection point of

the bracket in order to re-establish protection of the electrical circuit. The top connection point should be fitted with an additional fuse to protect the newly connected load.

Voltage V	Rated current A	Cross section mm ²	Cable Length mm	DU	Article no.
to 32	to 15	1,3	120	1	50390430



Low Profile MINI

Fuse Holder

Fuse type: for low profile mini blade fuse
Material: Polyamid 6.6
Surface: Tin-plated
Info: with connecting cable



Additional loads can be connected quickly and easily using the junction bracket. The fuse previously hidden in the fuse box is removed and replaced by the additional bracket. The fuse is then placed in the bottom connection point of

the bracket in order to re-establish protection of the electrical circuit. The top connection point should be fitted with an additional fuse to protect the newly connected load.

Voltage V	Rated current A	Cross section mm ²	Cable Length mm	DU	Article no.
to 58	to 10	1,3	120	1	50390447

MICRO2

Fuse Holder

Fuse type: for micro blade fuse
Material: Polyamid 6.6
Surface: Tin-plated
Info: with connecting cable



Additional loads can be connected quickly and easily using the junction bracket. The fuse previously hidden in the fuse box is removed and replaced by the additional bracket. The fuse is then placed in the bottom connection point of


the bracket in order to re-establish protection of the electrical circuit. The top connection point should be fitted with an additional fuse to protect the newly connected load.

Voltage V	Rated current A	Cross section mm ²	Cable Length mm	DU	Article no.
to 32	to 10	1,3	120	1	50390614

MEGA ATO MINI

Adapter, fuse

Fuse type: from mega to standard
Bore Distance: 50,8 mm



Ideal for integrating additional functions in a system with MEGA/BF2 fuse holders with a necessary fuse under 80 A. Also suitable for certain automatic fuses as well as standard fuses.

Voltage V	Rated current A	DU	Article no.
12 to 24	to 40	1	50390443



RepPipe Repair Set, wash water line



Damaged sections of washing water lines can be replaced quickly and easily using the repair kit. Corrugated pipe connecting pieces, mounting clips and seals in three different diameters, in addition to a 2.5-metre-long corrugated pipe, are all contained to repair corrugated pipelines with a nominal width of 4.5. In addition,

damaged sections of washing water lines made from smooth hoses can be repaired using connecting adapters with diameters of 3 mm and 4 mm. Moreover, hose fittings are contained for the direct connection of smooth hoses.

	Quantity	DU	Article no.
	159	1	54271025
Content		QU	
Assortment Box		1	99994521
Clip RepPipe		28	51271335
Connector, pipes RepPipe		6	51271320
		6	51271321
		8	51271330
Corrugated Pipe		1	51271140
Hose Connector RepPipe		10	51271310
		10	51271311
Seal Ring, corrugated pipe RepPipe		30	50280050
		30	50280055
		30	50280060
Accessories	see	DU	
Seal Ring, corrugated pipe RepPipe	Katalog04	50	50280061

RepPipe Repair Set, wash water line



Using the repair kit, a defective point in the washing water line can be quickly and easily replaced. Corrugated pipe connecting pieces, mounting clips and seals in four different diameters, in addition to a 50-centimetre-long

corrugated pipe, are all contained to repair the corrugated pipeline with a nominal width of 4.5.

	QU	DU	Article no.
	Set	1	54271026066
Content		QU	
Clip RepPipe		4	51271335
Connector, pipes RepPipe		2	51271330
Corrugated Pipe		1	51271140
Seal Ring, corrugated pipe RepPipe		2	50280050
		2	50280055
		4	50280060
		2	50280061



RepVac

Repair set, negative pressure line



Faulty negative pressure lines made from rubber and hard plastic can be replaced with a modern negative pressure corrugated pipe with the repair kit. The following are included for repairs: straight and angled negative pressure connectors for corrugated pipe with a nominal width of 4.5 for connections with 3-4 mm and 5-7 mm, in addition to corrugated pipe connecting pieces. The assortment also includes fixing clamps, retaining clips and a 2.5-m-long corrugated pipe. The area of use ranges from passenger cars and commercial vehicles to motorcycles and construction machinery. Application examples include negative

pressure connections on: air filter boxes, distributors, MAP sensors, pressure control valves, central locking systems, etc. Advantages of the repair kit:

- universally compatible
- better protection against pine marten bites
- permanently flexible and durable
- smaller diameter than rubber lines
- Replacement for negative pressure lines from older vehicles which are no longer available
- emergency fix in the event of breakdowns
- cheaper than moulded hoses

	Quantity	DU	Article no.
	89	1	54271035
Content		QU	
Assortment Box		1	99994521
Clamping Clip RepVac		20	50268610
Connector, pipes RepVac		8	51271340
		8	51271341
		8	51271342
		8	51271350
		8	51271351
		8	51271352
Corrugated Pipe		1	51271140
Holding Bracket RepVac		20	50267222
Accessories	see	DU	
Pliers, hose clamp	Katalog08	1	95922000



RepDPF

Repair set, pressure line

Material: Silicone
Temperature range: -40 to +350 °C
Chemical Properties: Oil resistant
Info: with connection line with protection hose with marten protection with clamps



Using this repair kit, defective connecting hoses between the diesel particle filter (DPF) and the differential pressure sensor can be quickly and simply replaced. Pine marten bites may also be responsible for damage, and not just mechanical and thermic influences. That's why this set is supplied with protective hoses that

are resistant to both high temperatures and pine marten bites. They protect the silicone pressure lines from external influences. The spring band clamps included in the scope of supply ensure that the hoses are held securely.

Pressure hose connector diameter mm	Scope mm	Length m	DU	Article no.
5 6,5	10,0 to 12,5 11,0 to 13,5 11,5 to 14,0 12,5 to 15,0	1	1	54271045
Accessories		see	DU	
Pliers, hose clamp		Katalog08	1	95922000

Assortment, hose connectors



The great advantage of the 60 hose connectors in this assortment is in the hexagonal intermediate piece. This intermediate piece serves as a holder for a conventional spanner and simultaneously functions as both a "finger extension" and a lever. Mounting is made considerably easier, especially in tight spaces and hard-to-reach areas. Furthermore, the intermediate piece offers the option of attaching

a cable tie to fix the hose in place. The travel stops at both ends also prevent the cable tie from slipping. In addition, the black colour of the oil-resistant connectors ensures that they blend in perfectly with the hoses usually found installed in vehicles. The connectors contained in the assortment box are suitable for connecting smooth hoses with an inner diameter of between 3 and 6 mm.

	Quantity	DU	Article no.
	60	1	54271300
Content		QU	
Adapter, hose connector		6	51271314
		6	51271315
		6	51271316
		6	51271317
		6	51271318
		6	51271319
Hose Connector		6	51271312
		6	51271313
Hose Connector RepPipe		6	51271310
		6	51271311



ClipFixbasic
ClipFixcycle
ClassicFixbasic
ClipFixtwins

Assortment, spacer



This assortment contains various elastomer spacers in the most typical sizes for each one. The branded ClassicFix and ClipFix spacers can be used as chafe protection, spacer or damper rings, or as line connectors in almost any vehicle. They are suitable for lines or hoses made of plastic, metal, elastomer and braided steel alike. The material ethylene propylene diene monomer rubber (EPDM) is characterised by its good weather- and ozone-resistance, and is suitable for use in a temperature range from -40 °C to +150 °C. The ClipFixbasic,

ClipFixcycle and ClipFixtwins variants are advanced developments of the ClassicFixbasic model. These products are fastenable and ideally suited for retrofitting in areas with restricted accessibility, among others. The repair-friendly handling, adhesive-free mounting and ease of removal are particular highlights of this range. The ClipFixtwins can connect multiple lines or hoses and are primarily used for holding lines and tolerance compensation for spacing.



	Quantity	DU	Article no.
	New 62	1	54230010
Content		QU	
Assortment Box		1	99994522
Spacer ClassicFixbasic (Poppe)		5	50230808
Spacer ClipFixbasic (Poppe)		4	50230210
		4	50230306
		4	50230308
		4	50230309
		2	50230311
		2	50230312
		5	50230313
		5	50230315
		5	50230318
		5	50230320
		5	50230324
Spacer ClipFixcycle (Poppe)		2	50230804
Spacer ClipFixtwins (Poppe)		5	50230817
		5	50230818



Attachment parts – Effortless fixing!



Body fasteners for a range of vehicle areas

Body fasteners that secure connections between the body and body panelling, amongst other things, are used in a wide range of vehicle areas. We offer the ClipFix product group for this application. It comprises a wide product range, which is specifically made up of clips, blind rivets, retaining clips, expanding rivets, screws and other body fasteners.

Passt immer!

Assortments

With our assortments, we offer a professional selection of our latest small parts, covering a multitude of everyday workshop applications. Delivered in a practical case, the required spare parts are always at hand in the workshop.



Professional range!
Compiled with
customers & workshops



Assortment, fuses
Low Profile MINI / Low Profile JCase
5 - 60 A
QU: 95

54295040



Assortment, fuses
MICRO2 / MICRO3
5 - 30 A
QU: 110

54295640



Assortment, fuses
ATO / MINI / MAXI
3 - 80 A
QU: 478

54296212



Assortment, fuses
ATO / Torpedo
1 - 40 A
QU: 354

54295011



Assortment, fuses
MAXI
20 - 100 A
QU: 24

54295540



Assortment, fuses
MINI
3 - 30 A
QU: 111

54295570



Assortment, circuit breakers
ATO
7,5 - 25 A
QU: 5

54295060



Assortment, circuit breakers
MINI
7,5 - 25 A
QU: 5

54295090



Assortment, crimp connectors
0,5 - 2,5 mm²
QU: 806

54254149



Assortment, crimp connectors

0,5 - 2,5 mm²
QU: 603

54254139



Assortment, crimp connectors

0,35 - 2,5 mm²
QU: 825

54254161



Assortment, heatshrink tube

3 : 1
QU: 130
with inner adhesive

51273003



Assortment, cable entry grommets

QU: 197

54280011



Assortment, squeeze connectors

1 - 6 mm²
QU: 250

54254700



Assortment, squeeze connectors

0,5 - 2,5 mm²
QU: 250

54254100



Assortment, squeeze connectors

0,5 - 6 mm²
QU: 420

54254110



Assortment, squeeze connectors

0,5 - 2,5 mm²
QU: 295

54254113



**Assortment, plug housing
DT**

-55 - 125 °C
QU: 236

54290600



**Assortment, plug housing
Superseal**

QU: 314

54290050



**Assortment, plug housing
Superseal**

QU: 580

54290150



Assortment, plug housings

QU: 558
suitable for VAG

54290200



Tools

Adapter, container (brake fluid filling)	74
Air Conditioning Cleaner/-Disinfecter	62
Ampere Pliers	64 - 65
Battery Charger	72
Crimping Pliers	53 - 54
Crimping Pliers Set	55
Crimpzange	52
Filler/Bleeder Unit, brake fluid	73
Gas Soldering Torch	66 - 67
Hand lamp	75
Hot Air Dryer	66
Installation Aid Set, air conditioning service unit	61
Leak Search Set, Air Conditioning	61
Leakage Detector, air conditioning	59 - 60
Magnetic Lift	74
Memory Saver	72
Mounting Wedge	51
Multimeter	64
Programming-/Diagnostic Unit, TPMS	56 - 58
Release Pliers, hose line	53
Release Tool Set	50
Release tool, housing	51
Spray Gun, air conditioning cleaner/-disinfectant	62
Squeeze Pliers	52
Start Aid Device	70 - 72
Test Lead Set	63
Tester, battery	67
Testing Unit, towbar socket	67
Vernier Calliper, brake disc thickness	73
Voltage Detector	65
Wheel Sensor, TPMS	57





» RELEASE TOOLS



Changing contacts, simply!

One look at the internal workings of modern cars and even a layman can see that everything relating to electrics has become finer and smaller. Where in the past, large connections could be opened using unconventional methods, special tools are now required to carry out this function. We offer you all the latest release tools in an assortment box, which also protects your blades from bending or breaking!



UnlocBox 4all

Release Tool Set



The triple set of release tools can be used to open the most common connections. The set includes three cable release tools with six blades for common crimp connectors. The tips of the tools are made from high-quality spring

band steel and have a tensile strength of approx. 1800 N/mm. This enables precise extraction.

				Quantity	DU	Article no.
				3	1	95945424
Content	Diameter mm	Socket Width mm	Plug Type	QU		
Release Tool, flat-/round plug (AMP Tyco CI 2 AMP Tyco Mate-N-Lok GHW RAM GHW RSA2)	1,5 3,5		Round Plug Round Connector Sleeve	1		95945337
Release Tool, flat-/round plug (AMP Tyco JPT AMP Tyco JT AMP Tyco SPT AMP Tyco ST)		2,8 4,8 5,8 6,3	Blade Terminal Blade Terminal Sleeve	1		95945335
Release Tool, flat-/round plug (AMP Tyco MT I AMP Tyco MT II)		1,6	Blade Terminal Blade Terminal Sleeve	1		95945336



www.herthundbuss.com/channel

Release tool, housing



Manufacturer Restriction:

VAG
FEP
Opel
Fiat

	DU	Article no.
	1	95945445



Mounting Wedge



Material:

Plastic

WxH:

27 x mm

Length mm	DU	Article no.
210	1	95926000



2



Squeeze Pliers



Example:



The crimping tool permits precise hexagonal crimping of ferrules with and without insulating collar. It is easy to work with ferrules with cross-sections of between 0.08 mm² and 16.0 mm² in one tool without the need for adjustment. With the swivel positioner fitted, accurate working is possible even for ferrules

with a small cross-section. The swivel positioner can be attached to the front or back of the tool to permit optimum right-handed and left-handed use of the tool. The small width of the handle, the low weight and the ergonomic, non-slip soft grips guarantee excellent handling of the tool.

Cross section: 0,08 to 16 mm²
Plug type: Cable End Sleeve
WxH: 75 x mm
Weight: 500 g
Tools: with positioner
Info: for unisolated contacts
for isolated contacts

Length mm	Profile	DU	Article no.
215		1	95942365



Squeeze Pliers



Example:



The squeeze pliers are suitable for work on non-insulated cable lugs (DIN 46234, DIN 46230, DIN 46341) with closed crimp sleeves. The unlockable lock system and ergonomically

formed soft hand grips ensure work is comfortable.

Cross section: 0,1 to 0,35 mm²
0,5 to 1,0 mm²
1,5 to 2,5 mm²
4 to 6 mm²
10 to 16 mm²
Plug type: Ring Connector
Weight: 470 g
Crimp form: W-shaped
Info: for unisolated contacts

Length mm	Profile	DU	Article no.
220		1	95942059

Crimping pliers



Cross section: 0,13 to 2,5 mm²
Plug type: Round Connector
Sleeve
Round Plug
Blade Terminal Sleeve
Blade Terminal
Pliers head surface: burnished
Weight: 200 g
WxH: 60 x mm
Tool Handle Colour: grey
Info: for unisolated contacts

Length mm	Profile	DU	Article no.
225		1	90942242

Release Pliers, hose line



Material: CrMo 4130 (chrome-molybdenum 4130) **WxH:** 94 x 202 mm

Length mm	DU	Article no.
202	1	95922003

CrimPro 10 Crimping Pliers



The CrimPro 10 offers a large range of processing options. Professional crimping precision for all common contacts thanks to linear die crimping. Ergonomic soft-hand grip also ensures fatigue-proof work. Inserts can be changed without additional tools.

Tools: Basic pliers without insert

Length mm	DU	Article no.	
155	1	95942330	
210	1	95942331	
Accessories	see	DU	
Crimping Pliers Insert	Katalog08	1	95942332
	Katalog08	1	95942346
	Katalog08	1	95942347
Crimping Pliers Insert (ABS - 24V)	Katalog08	1	95942350
	Katalog08	1	95942351
	Katalog08	1	95942354
	Katalog08	1	95942357
Crimping Pliers Insert (AMPTyco MT I AMPTyco MT II AMP Tyco JPT)	Katalog08	1	95942345
Crimping Pliers Insert (AMPTyco MT I ELA AMPTyco MT II ELA AMPTyco JPT ELA)	Katalog08	1	95942348
Crimping Pliers Insert (AMPTyco SPT 5,8 ELA)	Katalog08	1	95942126
Crimping Pliers Insert (AMPTyco Superseal)	Katalog08	1	95942349
Crimping Pliers Insert (GHW DFK 2)	Katalog08	1	95942353
Crimping Pliers Insert (GHW MDK 5 AMPTyco JPT)	Katalog08	1	95942352
Crimping Pliers Insert (GHW MDK 5 Plus GHW RSA 2 Plus)	Katalog08	1	95942359
Crimping Pliers Insert (KOSTAL MLK 1,2)	Katalog08	1	95942335
Crimping Pliers Insert DT (Deutsch DT Deutsch DTM)	Katalog08	1	95942358



www.herthundbuss.com/channel



CrimPro 30

Crimping Pliers



The crimping pliers CrimPro 30 fulfil the highest demands for quality and functional use. Intended for industrial use, different crimp sets can be used to process cross-sectional areas of 0.1 to 25 mm². Professional crimping precision for all common contacts thanks to linear die crimping. The double guide system guarantees an even application of clamping force and pre-

cise, torsion-resistant guiding in all profiles, thus ensuring that even the smallest tolerances are maintained. The unlockable positive lock and an integrated fold positioner enable optimal fixing of the contacts. An ergonomic soft-hand grip ensures fatigue-proof work.

Tools: Basic pliers without insert

Length mm	DU	Article no.		
220	1	95942166		
270	1	95942164		
Accessories	see	DU		
Crimping Pliers Insert	Katalog08	1	95942119	
	Katalog08	1	95942120	
	Katalog08	1	95942161	
	Katalog08	1	95942162	
	Katalog08	1	95942177	
	Katalog08	1	95942178	
	Katalog08	1	95942179	
	Katalog08	1	95942187	
	Katalog08	1	95942188	
	Crimping Pliers Insert (ABS - 24V)	Katalog08	1	95942185
		Katalog08	1	95942186
	Crimping Pliers Insert (AMPTyco JPT AMPTyco MCP 2,8)	Katalog08	1	95942192
	Crimping Pliers Insert (AMPTyco JPT ELA)	Katalog08	1	95942193
	Crimping Pliers Insert (AMPTyco MCP 1,5 ELA)	Katalog08	1	95942143
	Crimping Pliers Insert (AMPTyco MCP 1,5)	Katalog08	1	95942142
	Crimping Pliers Insert (AMPTyco MQS ELA)	Katalog08	1	95942182
	Crimping Pliers Insert (AMPTyco MQS)	Katalog08	1	95942181
	Crimping Pliers Insert (AMPTyco MT I AMPTyco MT I ELA AMPTyco MT II AMPTyco MT II ELA)	Katalog08	1	95942190
	Crimping Pliers Insert (AMPTyco Superseal)	Katalog08	1	95942189
	Crimping Pliers Insert (GHW DFK 2)	Katalog08	1	95942194
Crimping Pliers Insert (GHW MDK 5)	Katalog08	1	95942195	
Crimping Pliers Insert (KOSTAL DLK 1,2)	Katalog08	1	95942147	
Crimping Pliers Insert (KOSTAL LKS 1,5 ELA)	Katalog08	1	95942130	
	Katalog08	1	95942131	
	Katalog08	1	95942173	
Crimping Pliers Insert (KOSTAL LKS 1,5 ELA-U)	Katalog08	1	95942168	
Crimping Pliers Insert (KOSTAL LKS 1,5)	Katalog08	1	95942180	
Crimping Pliers Insert (KOSTAL MLK 1,2 ELA)	Katalog08	1	95942141	
Crimping Pliers Insert (KOSTAL MLK 1,2 ELA-U)	Katalog08	1	95942171	
	Katalog08	1	95942196	
Crimping Pliers Insert (KOSTAL MLK 1,2)	Katalog08	1	95942163	
	Katalog08	1	95942167	
Crimping Pliers Insert (KOSTAL MQ 0,6)	Katalog08	1	95942148	
	Katalog08	1	95942149	
Crimping Pliers Insert (KOSTAL SLK 2,8 KOSTAL SLK 2,8 ELA)	Katalog08	1	95942169	
Crimping Pliers Insert (KOSTAL SLK 2,8 ELA)	Katalog08	1	95942145	
	Katalog08	1	95942151	
	Katalog08	1	95942172	
Crimping Pliers Insert (KOSTAL SLK 2,8)	Katalog08	1	95942144	
	Katalog08	1	95942150	
	Katalog08	1	95942170	
Crimping Pliers Insert (KOSTAL SLK 5,8 ELA)	Katalog08	1	95942174	
	Katalog08	1	95942183	
Crimping Pliers Insert (KOSTAL SLK 5,8)	Katalog08	1	95942176	
	Katalog08	1	95942184	

CrimPro 35 Crimping Pliers Set



Example:



The CrimPro 35 crimping pliers are suitable for a wide range of applications. The tool's precise guidance slot guarantees high-quality results. The pliers are made from high-tensile steel. Parts which are subject to particular stress are specially annealed. The inserts can be changed easily. Thanks to the patented crimping insert fixing, the insert pairs can be easily and accurately interchanged, and an additional guidance slot is provided on the tool. The CrimPro 30 series inserts are compatible but can only be used without a positioner. The Crim-

Pro 35 requires a minimum of effort to operate due to its optimal force transmission characteristics. The crimping pliers set, with its insulation and separation mechanism, serves to process common connectors using the three crimping inserts contained in the set.

- insulated flat plugs and flat connector sleeves
- non-insulated flat plugs and flat connector sleeves
- non-insulated ring cable fittings in line with DIN 46 234

Cross section: 0,1 to 10 mm²
Plug type: Blade Terminal
 Blade Terminal Sleeve
 Ring Connector

Info: for isolated contacts
 for unisolated contacts

	Profile	DU	Article no.
		1	95942364

www.herthandbuss.com/channel





AirGuard

Programming-/Diagnostic Unit, TPMS



The AirGuard is a programming and diagnostic device. It allows work to be carried out directly on the vehicle whilst offline. The vehicle database, with a coverage of 80-90%, is stored in the device itself. Updates are available free of charge from our website. The AirGuard is able to read out all sensor types found on the market. Then, it is able to automatically or manually duplicate the read data to the Herth+Buss wheel sensors. Programming a new

sensor ID is also possible, as well as the wireless reprogramming of the sensor ID of activated Herth+Buss wheel sensors whilst fitted.

- Read-out of own/third-party sensors according to integrated database
- Programming of Herth+Buss wheel sensors according to integrated database
- free updates
- vehicle coverage of 80-90%
- vehicle data directly on the device

Screen Diagonal:
Terminal/Clamp:

2,5 Inch
with USB socket

Gauge:
Info:

with LCD display
with charger

	DU	Article no.
	1	95990001
Accessories	see	DU
OBD Adapter, TPMS AirGuard	Katalog08	1 95990003
Toolbox AirGuard	Katalog08	1 95990001010
Valve Repair Set (TPMS) AirGuard	Katalog08	4 70699433012
Valve, TPMS AirGuard	Katalog13	1 70699433013
	Katalog13	1 70699433014
	Katalog13	1 70699434013
Wheel Sensor, TPMS AirGuard	Page 57	1 70699434
	Page 57	1 70699443



www.herthundbuss.com/channel

AirGuard Wheel Sensor, TPMS



Herth+Buss wheel sensors can be used in all vehicles that have a tyre pressure monitoring system installed as standard. The AirGuard is required for programming and adjustment to the vehicle concerned. This process only takes between 5 and 15 seconds per sensor. An outstanding feature of the Herth+Buss wheel sensors: the original serial/ID number can be copied from the "old" sensor to the new one, or can be reassigned. In addition, the wheel sensors can be rewritten, used in aluminium and

steel rims and wirelessly activated. The sensors can be ordered individually and are supplied with the complete valve in standard silver. A valve repair kit is also available, as are replacement valves in silver and black.

- one for all: optimum stockage with just one universal wheel sensor
- valves with adjustable angles
- for steel or aluminium rims
- certification up to 250 km/h
- battery service life: 3-7 years

to Tightening torque:

4 Nm

Material:

Aluminium

Pressure:

to 9 bar

Weight:

46 g

only in connection with:

95990001

Info:

with battery
with pressure sensor
with integrated air
temperature sensor
with seal
with box nut
with screw
with valves

Frequency Range MHz	Information Transfer	DU	Article no.
433	Radio	1	70699443
Content			QU
Valve, TPMS AirGuard		1	70699433013
Accessories		see	DU
Programming-/Diagnostic Unit, TPMS AirGuard		Page 56	1 95990001
Valve Repair Set (TPMS) AirGuard		Katalog08	4 70699433012
Valve, TPMS AirGuard		Katalog13	1 70699433014

AirGuard Wheel Sensor, TPMS



This snap-in wheel sensor can be installed in both light alloy rims and steel rims and can be activated wirelessly. Please note that the permissible maximum speed is restricted to 210 km/h. Supplied with a rubber valve.

Herth+Buss wheel sensors can be used in all vehicles that have a tyre pressure monitoring system installed as standard. The AirGuard is required for programming and adjustment to the vehicle concerned. This process only takes between 5 and 15 seconds per sensor. An outstanding feature of the Herth+Buss wheel sensors: the original serial/ID number can be copi-

ed from the "old" sensor to the new one, or can be reassigned. In addition, the wheel sensors can be rewritten, and can be used in aluminium and steel rims. The sensors can be ordered individually and are supplied with a complete valve. A replacement valve is also available.

- one for all: optimum stockage with just one universal wheel sensor
- for steel or aluminium rims
- certification up to 210 km/h
- battery service life: 3-7 years

Material:

Steel Elastomer

Pressure:

to 9 bar

Weight:

36 g

only in connection with:

95990001

Info:

with battery
with pressure sensor
with integrated air
temperature sensor
with screw
with valves

Frequency Range MHz	Colour	DU	Article no.
433	●	1	70699434
Content			QU
Valve, TPMS AirGuard		1	70699434013
Accessories		see	DU
Programming-/Diagnostic Unit, TPMS AirGuard		Page 56	1 95990001





AirGuard

Programming-/Diagnostic Unit, TPMS

The starter set already contains the programming /diagnostic device, TPMS AirGuard and four wheel sensors. This makes it the perfect TPMS starter set.



Info: with pressure sensor
with valves

Frequency Range MHz	DU	Article no.
433	1	95990004
Content	QU	
Programming-/Diagnostic Unit, TPMS AirGuard	1	95990001
Wheel Sensor, TPMS AirGuard	4	70699443
Accessories	see	DU
OBD Adapter, TPMS AirGuard	Katalog08	1 95990003
Valve Repair Set (TPMS) AirGuard	Katalog08	4 70699433012
Valve, TPMS AirGuard	Katalog13	1 70699433013
	Katalog13	1 70699433014
	Katalog13	1 70699434013
Wheel Sensor, TPMS AirGuard	Page 57	1 70699434

AirGuard

Programming-/Diagnostic Unit, TPMS

The starter set already contains the programming /diagnostic device, TPMS AirGuard and the OBD-II module. This makes it the perfect TPMS starter set.




Info: with OBD connector

	DU	Article no.
	1	95990005
Content	QU	
OBD Adapter, TPMS AirGuard	1	95990003
Programming-/Diagnostic Unit, TPMS AirGuard	1	95990001
Accessories	see	DU
Valve Repair Set (TPMS) AirGuard	Katalog08	4 70699433012
Valve, TPMS AirGuard	Katalog13	1 70699433013
	Katalog13	1 70699433014
	Katalog13	1 70699434013
Wheel Sensor, TPMS AirGuard	Page 57	1 70699434
	Page 57	1 70699443

SelectH2

Leakage Detector, air conditioning



Selective hydrogen gas detector for effective and environmentally friendly leak detection in air-conditioning and cooling systems using forming gas. The SelectH2 is fitted with a suction pump and two sensors. These operate like an artificial nose and suck in the test gas. With the SelectH2 you have a time-saving and environmentally sustainable alternative solution, which can be used for testing even large HGV and bus air-conditioning systems economically. The forming gas 95/5 (95% nitrogen, 5% hydrogen) is also used as inert gas in welding and is generally readily available from any gas retailer. The leak detection method using forming gas also complies fully with directive 2006/40/EU on emissions from air-conditioning systems in motor vehicles. The ma-

nufacturer recommends annual calibration to guarantee the high precision of the device in the long term.

- maximum hit rate even with the smallest leaks
- recognise defective heat exchangers even without removing the dashboard
- only reacts to hydrogen and therefore prevents misdiagnoses due to oil and petrol vapours
- automatic zero-point calibration in fresh air
- concentration-dependent signal
- automatic sensor check with error detection
- plastic case with cushioned lid and gas-free insert (important for storage)

Long gooseneck: 320 mm
Head Width: 14 mm
Housing Type: Aluminium Housing
WxHxD: 52 x 178 x 35 mm

Workshop Equipment: for measurement of the hydrogen concentration with integrated suction pump

Gauge: with illuminated LCD display with LED display with acoustic alarm

Info: with acoustic alarm

			DU	Article no.
			1	95980002
Content	Diameter mm	Plug Type	QU	
Power Supply SelectH2	3,5	Round Plug	1	95980002001
Accessories		see	DU	
Adapter, air conditioning service unit SelectH2	Katalog08	1	95980027002	
	Katalog08	1	95980027003	
	Katalog08	1	95980027004	
	Katalog08	1	95980027005	
	Katalog08	1	95980027006	
Cylinder Pressure Regulator SelectH2	Katalog08	1	95980028002	
Filler Hose Set, air conditioning service unit SelectH2	Katalog08	1	95980027001	
Installation Aid Set, air conditioning service unit SelectH2	Page 61	1	95980027	



www.herthundbuss.com/channel





SelectH2 mini

Leakage Detector, air conditioning



Selective hydrogen gas detector for effective and environmentally friendly leak detection in air-conditioning and cooling systems using forming gas. The SelectH2 mini is equipped with two sensors (unique dual-sensor system). The device operates with diffusion technology and detects the hydrogen concentration in the gas cloud surrounding the leak. With the SelectH2 mini, you have a time-saving and environmentally sustainable alternative solution which can be used for testing even large HGV and bus air-conditioning systems economically. The forming gas 95/5 (95% nitrogen, 5% hydrogen) is also used as a shielding gas in welding and is generally readily available from any gas retailer. The leak detection method using forming gas also complies fully with directive 2006/40/EU on emissions from air-

conditioning systems in motor vehicles. The manufacturer recommends annual calibration to guarantee the high precision of the device in the long term.

- high hit rate even with the smallest leaks
- recognise defective heat exchangers even without removing the dashboard
- only reacts to hydrogen and therefore prevents misdiagnoses due to oil and petrol vapours
- automatic zero-point calibration in fresh air
- concentration-dependent signal
- automatic sensor check with error detection
- integrated LED light
- plastic case with cushioned lid and gas-free insert (important for storage)

Long gooseneck: 320 mm
Housing Type: Synthetic Material Housing
Required appliance battery: Nickel Metal Hydrid Battery (NiMH)
WxHxD: 44 x 170 x 40 mm

Workshop Equipment: for measurement of the hydrogen concentration

Gauge: with illuminated LCD display with battery status indicator

Info: with integrated work light with charger with acoustic alarm with case

Diameter mm	DU	Article no.		
2,5	1	95980019		
Content	Diameter mm	Plug Type	QU	
Power Supply	2,5	Round Plug	1	95980995
Accessories	see	DU		
Adapter, air conditioning service unit SelectH2	Katalog08	1	1	95980027002
	Katalog08	1	1	95980027003
	Katalog08	1	1	95980027004
	Katalog08	1	1	95980027005
	Katalog08	1	1	95980027006
Connector/Distributor Piece, compressed air system SelectH2	Katalog08	1	1	95980027008
Cylinder Pressure Regulator SelectH2	Katalog08	1	1	95980028002
Filler Hose Set, air conditioning service unit SelectH2	Katalog08	1	1	95980027001
Installation Aid Set, air conditioning service unit SelectH2	Page 61	1	1	95980027

SelectH2

Leak Search Set, Air Conditioning



Selective hydrogen gas detector for effective and environmentally friendly leak detection in air-conditioning and cooling systems using forming gas. The SelectH2 is fitted with a suction pump and two sensors. These operate like an artificial nose and suck in the test gas. With the SelectH2 you have a time-saving and environmentally sustainable alternative solution, which can be used for testing even large HGV and bus air-conditioning systems economically. The forming gas 95/5 (95% nitrogen, 5% hydrogen) is also used as inert gas in welding and is generally readily available from any gas retailer. The leak detection method using forming gas also complies fully with directive 2006/40/EU on emissions from air-conditioning systems in motor vehicles. The ma-

nufacturer recommends annual calibration to guarantee the high precision of the device in the long term.

- maximum hit rate even with the smallest leaks
- recognise defective heat exchangers even without removing the dashboard
- only reacts to hydrogen and therefore prevents misdiagnoses due to oil and petrol vapours
- automatic zero-point calibration in fresh air
- concentration-dependent signal
- automatic sensor check with error detection
- plastic case with cushioned lid and gas-free insert (important for storage)

		QU	DU	Article no.	
			Set	1	95980028
Content	Diameter mm	Plug Type	QU		
Adapter, air conditioning service unit SelectH2			1		95980027004
			1		95980027005
Cylinder Pressure Regulator SelectH2			1		95980028002
Installation Aid Set, air conditioning service unit SelectH2			1		95980027
Leakage Detector, air conditioning SelectH2			1		95980002
Power Supply SelectH2	3,5	Round Plug	1		95980002001
Toolbox SelectH2			1		95980028001
Accessories		see	DU		
Adapter, air conditioning service unit SelectH2		Katalog08	1		95980027006



www.herthundbuss.com/channel

SelectH2

Installation Aid Set, air conditioning service unit



Number of ports: 3
Port Thread: SAE

Outer thread:

1/4 Inch

Operating pressure bar	DU	Article no.	
to 38	1	95980027	
Content	QU		
Adapter, air conditioning service unit SelectH2	1	95980027002	
	1	95980027003	
Filler Hose Set, air conditioning service unit SelectH2	1	95980027001	
Accessories	see	DU	
Adapter, air conditioning service unit SelectH2	Katalog08	1	95980027004
	Katalog08	1	95980027005
	Katalog08	1	95980027006
Connector/Distributor Piece, compressed air system SelectH2	Katalog08	1	95980027008
Cylinder Pressure Regulator SelectH2	Katalog08	1	95980028002



AirClean

Spray Gun, air conditioning cleaner/-disinfectant



With AirClean, we are expanding our portfolio of A/C system maintenance products. In addition to leak detection, AirClean allows us to offer the option of disinfecting the vehicle and its A/C system without a great deal of effort and without harming the environment. AirClean is suitable for all vehicles, cars, vans, HGVs, mobile homes etc.
How much air-conditioning cleaner is required

for each application and each type of vehicle? The consumption rates for air-conditioning cleaner are as follows:

- Small car: application time 5 minutes; consumption 70 ml
- Medium-sized car: application time 10 minutes, consumption 100 ml
- Van/SUV/minibus: application time 12 minutes; consumption 120 ml

Hose length: 2,5 m **Info:** with hose
Weight: 600 g with handle

	DU	Article no.
	NEW	1
	1	95921003
Accessories	see	DU
Air Conditioning Cleaner/-Disinfecter AirClean	Page 62	1
		95923008
for article number		
95923008		



AirClean

Air Conditioning Cleaner/-Disinfecter



AnoKath is a powerful oxidising agent made from water and sodium chloride. The agent is used to disinfect vehicle A/C systems or the vehicles themselves with the help of the special AirClean cold nebulisers. It reliably reduces

germs, viruses and bacteria. The disinfection process using AnoKath is based on minerals.

Material: Plastic

Operating temperature °C	Ambient temperature °C	Contents ml	DU	Article no.
20 to 25	5 to 25	1000	1	95923008
Accessories		see	DU	
Spray Gun, air conditioning cleaner/-disinfectant AirClean		Page 62	1	95921003

TesTip

Test Lead Set



TesTip is a set of different measuring cable sets, which enables simplified troubleshooting and secure signal pick-up through direct contact in electric vehicle components. The 94-part case set contains various adapters (measuring cable sets). The set also includes polarity tester which can be used to test Hall and photo-

sensors and determine positive or earth-controlled injectors. Measuring potentiometers for checking temperature sensors, fuel sensors and throttle valve position sensors are included. The contained measuring resistors enable airbag circuits to be checked. All individual components can be adjusted.

				Quantity	DU	Article no.
				94	1	95980778
Content	Diameter mm	Socket Width mm	Plug Type	QU		
Multimeter Holding Wire TesTip		0,8	Blade Terminal	3		95980778018
		0,8	Blade Terminal Sleeve	3		95980778019
		1,2	Blade Terminal	4		95980778020
		1,2	Blade Terminal Sleeve	4		95980778021
		2,0	Blade Terminal	4		95980778022
		2,0	Blade Terminal Sleeve	4		95980778023
		2,5	Blade Terminal	3		95980778024
		2,5	Blade Terminal Sleeve	3		95980778025
		3,0	Blade Terminal	4		95980778026
		3,0	Blade Terminal Sleeve	4		95980778027
		5,0	Blade Terminal	3		95980778028
		5,0	Blade Terminal Sleeve	3		95980778029
		6,0	Blade Terminal	3		95980778030
		6,0	Blade Terminal Sleeve	3		95980778031
		1,5	Round Connector Sleeve	3		95980778011
		1,5	Round Plug	3		95980778010
		2	Round Connector Sleeve	3		95980778013
		2	Round Plug	3		95980778012
		3,5	Round Connector Sleeve	3		95980778015
		3,5	Round Plug	3		95980778014
	4	Round Connector Sleeve	3		95980778017	
	4	Round Plug	3		95980778016	
	4,5			4	95980778008	
Plug Distributor TesTip				2		95980778007
Polarity Tester TesTip				2		95980778002
Potentiometer TesTip				2		95980778001
Probe, multimeter TesTip				2		95980778005
				4		95980778006
				2		95980778009
SRS Plug, test resistor TesTip				2		95980778003
Terminal, electric universal parts TesTip				2		95980778004



2



www.herthundbuss.com/channel



Multimeter



The digital multimeter is an essential assistant in every workshop. It measures electrical values such as voltages and frequencies. The multimeter is also designed for temperature measurement in air-conditioning systems. It has automatic or manual measurement settings. It has a Data Hold function, i.e. various readings can be frozen during the measurement process and retrieved as and when required. You can also use the multimeter to detect the cam angle of the ignition timer shaft on ignition timer systems of all standard four-stroke multi-cylinder engines. The same app-

lies for reading engine speeds. It has an clear, easy-to-read illuminated LCD display. The multimeter can withstand knocks and dropping because there are no moving parts to damage. It is therefore ideal for intensive workshop use.

- automatic or manual selection of measurement range
- automatic switch-off after 30 minutes idle
- values saved (data hold)
- cam angle and speed measurement
- delivery includes measurement cable, temperature sensor and battery

Duty cycle: 5 to 95 %
Registration Type: CE approved
Required appliance battery: 9V Block
WxHxD: 83 x 165 x 47 mm

Weight: 370 g
Gauge: with illuminated LCD display
Info: with diode test function with continuity test function

Measurement range (AC) V	Measurement range (DC) V	Measurement range Ω	Measurement range Hz	Measurement range °C	DU	Article no.
4 40 250	0,4 4 40 250	400 Ohm to 40 MOhm	5 Hz to 200 kHz	-20 °C to +1000 °C	1	95980775
Content		Rated current A	Number of Poles terminal	Diameter mm	QU	
Fuse		0,5		5	1	50295044
Temperature Probe, multi-meter			2		1	95980775001
Accessories				see	DU	
Ampere Pliers Claw 400				Page 65	1	95980785
Test Lead Set TesTip				Page 63	1	95980778



www.herthundbuss.com/channel

Claw 100

Ampere Pliers



Especially suited to precise measurements in the lower current area. This allows closed current measurements to be conducted without having to separate the circuit.


- automatic selection of measurement range

- automatic switch-off after 15 minutes idle
- values saved (data hold)
- delivery includes measuring cable and bag

Registration Type: CE approved
 GS checked
 AAA (Micro)
Required appliance battery: Nickel Metal Hydrid Battery (NiMH)
WxHxD: 71 x 226 x 38 mm

Weight: 200 g
Gauge: with LCD display
Info: with diode test function with continuity test function

Measurement range (AC) V	Measurement range (DC) V	Measurement range (AC) A	Measurement range (DC) A	Measurement range Ω	DU	Article no.
4 40 400 600	0,4 4 40 400 600	40 100	40 100	400 Ohm to 40 MOhm	1	95980776



www.herthundbuss.com/channel

Claw 400

Ampere Pliers



The clamp meter is suitable for measuring high flows up to 400 amperes.

- measurement of AC/DC current
- with zero point key
- bag included in delivery

Required appliance battery: 9V Block
WxHxD: 73 x 186 x 40 mm
Cable Length: 2,3 m
Weight: 300 g

additionally required parts: Multimeter
Gauge: with battery status indicator
Info: with banana plug

Measurement range (AC) A	Measurement range (DC) A	DU	Article no.
40 400	40 400	1	95980785
Accessories		see	DU
Multimeter		Page 64	1 95980775



PlusMinus 3-28

Voltage Detector



The voltage detector PlusMinus 3-28 is compatible with electronic components like engine control units, sensors etc. An earth line or -terminal is not required.

Direct current: 3 to 28 V
Registration Type: CE approved
Surface: Chromed
Housing Type: Metal Housing

Required appliance battery: N (Lady)
Gauge: with LED display
Info: with acoustic alarm



Length mm	Diameter mm	DU	Article no.
150	20	1	90940110





HeatGun

Hot Air Dryer



The HeatGun is an indispensable aid for many applications and is suitable for professionally working with shrink tubing and shrink connectors for example. The various attachments ensure greater precision and accurate control of the hot air to suit the application concerned. Further features include:

- infinitely variable temperature regulation
- six blower speed settings
- LCD temperature display
- stand for stationary working
- supplied complete with four different attachments

Input Voltage:
Rated Power:

230 V
2000 W

Mains Cable Length:
Gauge:

1,8 m
with LCD display

Temperature range °C	Connector	DU	Article no.
+50 to +600		1	95920000
Content		QU	
Attachment Set, hot air dryer HeatGun		1	95920000001

Burner

Gas Soldering Torch



Thanks to the adjustable gas supply and the attachments included in the scope of delivery, the burner is suitable for a wide variety of operations, such as for professional heating of shrink tubing or soldering in cable lugs.

- with piezo ignition
- refilling with commercially available

- butane gas cartridges for cigarette lighters
- with stand
- inspection port for checking gas level
- including solder wire coil (lead-free), sponge, various attachments and a handy plastic box

Operating time to:

75 min.

Fuel Tank Volume:

30 ml

Solder Temperature °C	Flame temperature °C	Hot Air Temperature °C	DU	Article no.
450	1300	600	1	95921001
Content			QU	
Attachment Set, gas soldering torch			1	95921001001

Gas Soldering Torch



Operating time to: 60 min. Fuel Tank Volume: 12 ml

Solder Temperature °C	Flame temperature °C	Hot Air Temperature °C	DU	Article no.
350	1300	550	1	95921000
Accessories			see	DU
Attachment Set, gas soldering torch			Katalog08	1
				95921001001

CrankPrint

Tester, battery



This testing unit has been developed for testing starter batteries and for testing the starter and charge system in motor vehicles. Thanks to the advanced conductivity measurement method, the cold- start performance and/or the general state (starting capability) of a starter battery can be determined precisely, reliably and safely without placing an unnecessary strain on it. Alongside vehicle workshops, users also include manufacturers of automobi-

les and batteries in addition to battery dealers. It is suitable for AGM, spiral, flat-plate, gel, EFB and conventional wet-cell batteries.

- With an integrated thermal printer
- Direct detection of defective battery cells
- Automatic temperature compensation
- Reverse polarity protection for the appliance and battery
- Also tests discharging batteries
- Saves the last 100 test results

Rated Voltage: 6 V
12 V
Required appliance battery: 9V Block
WxHxD: 102 x 245 x 64 mm

Cable Length: 1,08 m
Workshop Equipment: with integrated thermal printer

with reverse polarity protection
Gauge: with illuminated LCD display

Measurement range according to SAE CCA	Language Version	Test standard	DU	Article no.
100 to 2000	English German Spanish Italian French	SAE DIN EN JIS IEC GB MCA BCI	1	95972081
Content			Length m	QU
Paper Roll, battery tester			6,4	1
				95972081001

Blinker

Testing Unit, towbar socket



The indicator enables both the assignment of the trailer socket and the lighting function of the trailer to be checked by just one person. The tester replaces and simulates the towing vehicle or the trailer as desired. The user can have the lighting signals of the vehicle displayed on the remote control or use the remote control to activate all lights on the trailer.

- one-man operation via radio, saving a lot of time
- suitable for CAN Bus Check Control System
- Vehicle and trailer can be tested independently of each other
- automatic switch-off after 5 minutes idle

Rated Voltage: 12 V
Number of Poles: 7 terminal
13 terminal
DIN / ISO: 1724
11446
72570
72577
Registration Type: CE approved

Battery: AGM Battery
Trailer Hitch: for trailer socket/trailer connector
Gauge: with LED display
Info: with remote control

Information Transfer	DU	Article no.
Radio	1	95980571



» REANIMATOR



For quick starters who want something extra!

Our Reanimator starting aid devices make starting the vehicle possible, even with a removed or defective battery. The battery in the unit allows the vehicle to be started from its own power.



	Reanimator Surge	Reanimator 1400	Reanimator Compact	Reanimator 2300
Start Aid Device	95980800	95980700	95980801	95980804
Rated Voltage	12 V	12 V	12 V	12 V
Peak Current	800 A	1400 A	1600 A	2300 A
Start Current	400 A	700 A	450 A	900 A
Gauge	with LED-display, load status display	with LED-display, battery status indicator, load status display	with LED-display, battery status indicator, load status display	with digitaler display, battery status indicator, load status display
Cable Length	330 mm	420 mm	450 mm	1590 mm
Cable Cross Section	13 mm ²	20 mm ²	16 mm ²	21 mm ²
Battery	-	LFP Battery (LiFePO4)	AGM-Battery	AGM-Battery
Battery Capacity	-	8 Ah	14 Ah	22 Ah
Weight	2.0 kg	3.5 kg	6.0 kg	10.8 kg
Combi Switch Function	On/Off switch	On/Off switch	-	On/Off switch
Terminal/Clamp	with USB socket	with USB socket	with USB socket	with USB socket
with cigarette lighter socket		■		■
with cigarette lighter plug	■	■		
reverse polarity protection	■	■		■
with integrated work light		■		
with capacitor	■			
Scope of application				
Suitable for				

» REANIMATOR



	Reanimator Hybrid	Reanimator 4600	Reanimator Trolley
Start Aid Device	95980802	95980805	95980803
Rated Voltage	12 V	12/24 V	12/24 V
Peak Current	3850 A	4600 A(12 V)/ 1800 A(24 V)	6200 A(12 V)/ 3100 A(24 V)
Start Current	1350 A	2300 A(12 V)/ 900 A(24 V)	2340 A(12 V)/ 1170 A(24 V)
Gauge	with LED-display, battery status indicator, load status display	with digitaler display, battery status indicator, load status display	with digital-display, battery status indicator, load status display
Cable Length	800 mm	1590 mm	1700 mm
Cable Cross Section	25 mm ²	21 mm ²	50 mm ²
Battery	AGM-Battery	AGM-Battery	AGM-Battery
Battery Capacity	22 Ah	22 Ah	50 Ah
Weight	11.7 kg	18.0 kg	35.7 kg
Combi Switch Function	On/Off switch	On/Off switch	On/Off switch, selector switch
Terminal/Clamp	-	with USB socket	-
with cigarette lighter socket	■	■	■
with cigarette lighter plug			
reverse polarity protection	■	■	■
with integrated work light			
with capacitor	■		
Scope of application			
Suitable for			





Reanimator 1400

Start Aid Device



Rated Voltage:	12 V	Output current USB:	2100 mA
Start Current:	700 A	WxHxD:	Width [mm] x 240 x 250 mm
Peak Current:	1400 A	Cable Length:	420 mm
Battery Capacity:	8 Ah	Cable Cross Section:	20 mm ²
IP-Code:	IP 20	Weight:	3,5 kg
Registration Type:	CE approved	Workshop Equipment:	with reverse polarity protection
Battery:	LFP Battery (LiFePO4)	Combi Switch Function:	On/Off Switch with LED display
Terminal/Clamp:	with USB socket	Gauge:	with load status display
Output Voltage USB:	5 V	Info:	with integrated work light
			with charger with cigarette lighter socket
			with cigarette lighter plug

	DU	Article no.
	1	95980700
Content	QU	
Battery Charger Reanimator 1400	1	95980700001
Accessories	see	DU
Memory Saver Keeper 5	Page 72	1 95980706



www.herthundbuss.com/channel

Reanimator Compact

Start Aid Device



A professional starting-aid battery for daily workshop use. This model is characterised by powerful performance despite its compact dimensions.

- Very compact and very light

- Powerful, maintenance-free and high-quality AGM battery
- With automatic high-frequency charger which is suitable for permanent connection

Rated Voltage:	12 V	WxHxD:	180 x 290 x 170 mm
Start Current:	450 A	Cable Length:	450 mm
Peak Current:	1600 A	Cable Cross Section:	16 mm ²
Battery Capacity:	14 Ah	Weight:	6,0 kg
Battery:	AGM Battery	Gauge:	with LED display
Terminal/Clamp:	with USB socket		with load status display
			with battery status indicator
		Surge protection:	Yes

	DU	Article no.
	1	95980801

Reanimator 2300

Start Aid Device



Rated Voltage:	12 V	Cable Cross Section:	21 mm ²
Start Current:	900 A	Weight:	9,8 kg
Peak Current:	2300 A	Gauge:	with digital display with battery status indicator
Registration Type:	CE approved		with load status display
Battery:	AGM Battery		300 A
Terminal/Clamp:	with USB socket		Yes
WxHxD:	340 x 410 x 140 mm	Protection:	
Cable Length:	1,44 m	Reverse polarity protection:	
		Fuse Type:	Melting Fuse

	DU	Article no.
	1	95980804

Reanimator Hybrid

Start Aid Device



The stand-out feature of this model is its hybrid construction, which has two different energy stores. In addition to featuring a leak-proof, high-performance AGM battery, the Reanimator Hybrid is also equipped with supercaps (ultracapacitors). The combination of

these energy stores enables a very high inrush current – particularly in the starting range. Furthermore, the capacitors absorb the main loads, thus conserving the battery. As such, they have a positive effect on the battery's service life.

Rated Voltage:	12 V	Weight:	11,7 kg
Start Current:	1350 A	Workshop Equipment:	with reverse polarity protection
Peak Current:	3850 A	Combi Switch Function:	On/Off Switch
Battery Capacity:	22 Ah	Gauge:	with LED display with load status display
Battery:	AGM Battery		with battery status indicator
WxHxD:	330 x 390 x 220 mm	Protection:	20 A 500 A
Cable Length:	800 mm	Surge protection:	Yes
Cable Cross Section:	25 mm ²	Fuse Type:	Standard Automatic Circuit Breaker Melting Fuse with cigarette lighter socket
		Info:	

	DU	Article no.
	1	95980802

Reanimator 4600

Start Aid Device



Rated Voltage:	12 V 24 V	Cable Length:	1,46 m
Start current:	1800 A 900 A	Cable Cross Section:	33 mm ²
Peak current:	4600 A 2300 A	Weight:	18,9 kg
Registration Type:	CE approved	Gauge:	with digital display with load status display with battery status indicator
Battery:	AGM Battery	Protection:	500 A
Terminal/Clamp:	with USB socket	Reverse polarity protection:	Yes
WxHxD:	340 x 410 x 200 mm	Fuse Type:	Melting Fuse

	DU	Article no.
	1	95980805





Reanimator Surge

Start Aid Device



In contrast to conventional assisted start devices, this device does not have an internal battery. Very powerful capacitors instead serve as power accumulators. These can store and then dispense the power required to start the engine in a very short time. The device functions entirely off-grid and can even be charged using the residual power from the discharged

vehicle battery in the worst-case scenario.

- extremely fast charging
- compatible with all 12 V starting systems
- entirely maintenance-free
- microprocessor controller
- reliable spark suppression, no arcing
- suitable for use down to -40°C
- no loss of power in freezing conditions

Rated Voltage: 12 V
Start Current: 400 A
Peak Current: 800 A
Operating Mode: Capacitor Operation
WxH: 190 x 63 x mm
Cable Length: 330 mm

Cable Cross Section: 13 mm²
Weight: 2 kg
Workshop Equipment: with reverse polarity protection
Gauge: with LED display
Info: with load status display
with hollow plug socket
with cigarette lighter socket

Length mm	DU	Article no.
235	1	95980800
Content	QU	
Charger Cable, cigarette lighter Reanimator Surge	1	95980800001

Flash CS120

Battery Charger



The to date most powerful battery charger from the Flash series and one of the strongest battery chargers on the market. The Flash CS120 battery charger is the perfect solution for charging batteries and supplying energy to the onboard power system during diagnostic

work and software updates. Any workshop with the CS120 battery charger can rely on being equipped for future energy requirements in the medium term. This charger features a regeneration mode and is also suitable for lithium batteries.

Rated Voltage: 12 V
Max. Charging Current: 120 A
IP-Code: 20
Registration Type: CE approved
WxHxD: 350 x 450 x 150 mm
Mains Cable Length: 1,7 m

Charger Cable Length: 6 m
Cable Cross Section: 25 mm²
Weight: 8,8 kg
Regeneration mode: Yes
Gauge: with digital display
with LED display

	DU	Article no.
	1	95950005

Keeper 5

Memory Saver



The Keeper 5 power save system supplies the vehicle with power while the battery is being replaced to ensure that various settings, such as radio codes, seat memory etc., are retained.

- simple connection via the OBD socket

- can be used together with any standard start booster

Rated Voltage: 12 V
Version: OBD II
Cable Length: 2,3 m

Gauge: with LED display
Info: with cigarette lighter socket

	DU	Article no.		
	1	95980706		
Content	Rated current A	Diameter mm	QU	
Fuse	5	6,3	1	50295150
Accessories		see	DU	
Socket		Katalog04	1	51306346
for article number				
95980700				



Filler/Bleeder Unit, brake fluid



This tool is used to bleed brake or clutch hydraulics. For this purpose, the tool is connected to the hydraulic system via the compensating reservoir. The reservoir is pressurised by means of the integrated hand pump. On bleeding (on opening the bleeder nipple), the brake fluid is forced through the hydraulic pipes and replaced with an adequate

- amount of fresh fluid.
- suitable for mobile use as no power or compressed-air connection is required
- one-man operation
- standard compressed-air connection, thus permitting the use of existing adapters
- supplied together with collector

Hose length: 1 m
Hose diameter: 7,5 mm
Material: Plastic

Workshop Equipment: with hand pump
Valve Type: With Pressure Relief Valve
Coupling type: Quick Coupling

Operating pressure bar	Contents, storage container l	DU	Article no.
0 to 1,4	3	1	J9300001



Vernier Calliper, brake disc thickness



Material: Aluminium

Measurement range mm	Measuring accuracy +/- mm	Length mm	DU	Article no.
0 to 50	0,25	395	1	J9330000



**Adapter, container (brake fluid filling)****Thread Size:**

M79x3

Surface:

Anodized

M46,5x3

Material:

Aluminium



	QU	DU	Article no.
	Set	1	J9300002
Accessories	see	DU	
Filler/Bleeder Unit, brake fluid	Page 73	1	J9300001
for article number			
J9300001			



2

Magnetic Lift

The magnetic lifter is ideally suited for safely removing oil drain screws. After the hot oil drain screw has been loosened slightly, it can be removed effortlessly using the magnetic attraction of the tool. This makes burning and

contamination a thing of the past.

Magnetic lift type:

Flexible

Info:for oil drain screw
magnetic

Length mm	Diameter mm	DU	Article no.
285	17,9	1	95922001

LED Shine Bump

Hand lamp

LED



If the area to be lit is small and requires focused light, the LED Shine Bump portable lamp is the perfect choice. Two lamps - a head lamp and a main lamp - are integrated in the lamp body. This means that the lamp can be used flexibly depending on the space requirements and illumination angle. The removable

magnet is another useful feature. The magnet can be used to mount the lamp on a variety of different surfaces. It can be easily removed in situations where contact with magnet-sensitive areas, such as close to sensors, is to be avoided.

Input Voltage:	230 V	Battery capacity:	1000 mAh
Light Design:	LED	Mounting Type:	Magnet Mount
IP-Code:	IP 65	Info:	with charger
Battery:	Li-Ion Battery		with mini USB plug
	with load status display		

Length mm	Number of LEDs	Lumen lm	Burn Time Hrs.	Charging time Hrs.	DU	Article no.
185	1 2	45 90	3,5 6	1	1	99910215

LED Shine Flex Pro

Hand lamp

LED



Rated Voltage:	12 V	Battery:	Li-Ion Battery
Light Design:	LED		with load status display
IP-Code:	IP 24	Mounting Type:	Magnet Mount
Material:	Plastic	Info:	with charger
			with hook
			with cigarette lighter socket

Length mm	Number of LEDs	Lumen lm	Burn Time Hrs.	Charging time Hrs.	DU	Article no.
230	5 21	50 150	4,5	3,5	1	99910212

Shine 3,5W

Hand lamp

LED



Voltage:	230 V	Cable ID:	H05RN-F 2x0,75mm ²
Rated Power:	3,5 W	Mains Cable Length:	5 m
Light Design:	LED	Mounting Type:	Glued
IP-Code:	IP 20	Info:	with handle
Plug type:	Euro flat plug		with hook

Length mm	Temperature range °C	Number of LEDs	Lumen lm	Connector	DU	Article no.
420	0 to +40	16	400		1	99910245





Electrics

Control Unit, lights	79
Marten Repellent	78
Time Relay	80 - 81





Shocker 80

Marten Repellent



IP-Code: IP 44 Info: with LED
WxHxD: 70 x 45 x 50 mm

Sound Level dB(A)	Rated Voltage V	Temperature range °C	Charging Rate mA	Cable Length mm	DU	Article no.
80	12	-40 to +82	20	300 600	1	59415053
Content				Rated Voltage V	QU	
Marten Repellent Shocker 80				12	10	59415051
Accessories				see	DU	
Screw				Page 26	5	52285560

Shocker 80

Marten Repellent



In order to achieve better protection against martens, a marten repellent should be installed on every entrance hole in the engine compartment. The installation location should be as deep as possible. The device operates in a 12-second cycle (see LED). The device should be installed so that the picture of the marten can be seen through the entrance hole. Should

there be multiple holes, a device should be installed on every side of the engine. The engine must be washed prior to installation or after each time a marten is present, in order to remove scent traces. With a power requirement of approx. 20 mA, the battery will not be discharged. The signal is inaudible to the human ear.

IP-Code: IP 44 Info: with LED
WxHxD: 70 x 45 x 50 mm

Sound Level dB(A)	Rated Voltage V	Temperature range °C	Charging Rate mA	Cable Length mm	DU	Article no.
80	12	-40 to +82	40	300 600	1	59415051
Accessories				Voltage V	see	DU
Fuse				to 250	Katalog04	10 50295050
Screw				Page 26	5	52285560

Shocker 110

Marten Repellent



More power – More protection – More safety A sound reflection system is used for the first time in a marten repellent. This makes it possible to achieve 360° emission. A convex cone is arranged above a piezoelectric loudspeaker with a NAWI membrane. The cone has the

same shape and diameter as the membrane. This design generates a high noise pressure and a 360° emission. The system operates in approx. 12-second cycles (on/off). The engine must be washed before installing the device.

WxHxD: 70 x 92 x 50 mm Info: with LED

Sound Level dB(A)	Rated Voltage V	Temperature range °C	Charging Rate mA	Cable Length m	DU	Article no.
110	12	-40 to +80	110	1,00	1	59415052
Accessories				see	DU	
Screw				Page 26	5	52285560

Control Unit, lights



Dummy resistance load for adapting LED trailer lights on vehicles with lamp monitoring. The failure of one LED unit is detected and the load is switched off.

- simple connection thanks to pre-installed cable with plug and socket
- LED failure is detected
- Short circuit is detected

- Controls all branches with shunt resistors
- LED-Adapt must be mounted on a metallic surface
- It is not permissible to connect bulbs to the outlet
- Under certain circumstances, the short circuit protection may only shut off after several minutes

IP-Code: IP 68
Information Suitable for CAN bus systems
Transfer:
Light Function: for taillight (LED)
for brake light (LED)
for rear fog light (LED)
for reverse light (LED)
for indicator (LED)
DIN / ISO: 1724 N-Typ

housing material: Aluminium
WxHxD: 232 x 49,5 x 102 mm
Number of Poles: 7 terminal

Rated Voltage V	Temperature range °C	Cable Length m	Connector	DU	Article no.
12	-40 to +55	0,5 2,5		1	76121254

Control Unit, lights



Dummy resistance load for adapting LED trailer lights on vehicles with lamp monitoring. The failure of one LED unit is detected and the load is switched off.

- simple connection thanks to pre-installed cable with plug and socket
- LED failure is detected
- Short circuit is detected

- Controls all branches with shunt resistors
- LED-Adapt must be mounted on a metallic surface
- It is not permissible to connect bulbs to the outlet
- Under certain circumstances, the short circuit protection may only shut off after several minutes

IP-Code: IP 68
Information Suitable for CAN bus systems
Transfer:
Light Function: for taillight (LED)
for brake light (LED)
for rear fog light (LED)
for reverse light (LED)
for indicator (LED)
DIN / ISO: 11446



housing material: Aluminium
WxHxD: 232 x 49,5 x 102 mm
Number of Poles: 13 terminal

Rated Voltage V	Temperature range °C	Cable Length m	Connector	DU	Article no.
12	-40 to +55	0,5 2,5		1	76121255





Time Relay





With adjustable time relays with a switch-on delay, the precise delay time can be set within the selected time range using a potentiometer. There are five time ranges to choose from as standard. Function: operating voltage at terminal

30. Voltage at terminal 15 means that the relay is switched on with a delay after the set time. If the voltage is removed from terminal 15, the relay switches off immediately.

Rated current: 10 A
Terminal/Clamp: Supply terminal 15
IP-Code: IP 54
WxHxD: 30 x 40 x 30 mm
Number of Poles: 5 terminal
Info: Switch-on delay

Plug type	Rated Voltage V	Port Type	adjustment range sec	DU	Article no.
BladeTerminal	12	5 x 6,3 mm	1 to 30	1	75614203
			30 to 900	1	75614069
Accessories			see	DU	
Relay Socket			Katalog04	5	50290266

Time Relay





With adjustable time relays with a switch-on delay, the precise delay time can be set within the selected time range using a potentiometer. There are five time ranges to choose from as standard. Function: operating voltage at terminal

30. Voltage at terminal 15 means that the relay is switched on with a delay after the set time. If the voltage is removed from terminal 15, the relay switches off immediately.

Rated current: 10 A
Terminal/Clamp: Supply terminal 30
IP-Code: IP 54
WxHxD: 30 x 40 x 30 mm
Number of Poles: 5 terminal
Info: Switch-on delay

Plug type	Rated Voltage V	Port Type	adjustment range sec	DU	Article no.
BladeTerminal	12	5 x 6,3 mm	1 to 30	1	75614205
			30 to 900	1	75614003
Accessories			see	DU	
Relay Socket			Katalog04	5	50290266

Time Relay





With adjustable time relays with a switch-off delay, the precise delay time can be set within the selected time range using a potentiometer. There are five time ranges to choose from as standard. Function: operating voltage at terminal 15. Voltage at terminal 15 means that the relay is switched on immediately. If the voltage

is removed from terminal 15, the relay is switched off after the set time has elapsed. In a time relay with diodes, the relay does not consume any closed current after being switched off due to the diode circuitry. Applications: delayed switch-off for fans and lighting

Rated current: 10 A
IP-Code: IP 54
WxHxD: 30 x 40 x 30 mm
Number of Poles: 5 terminal
Info: Switch-off delay

Plug type	Rated Voltage V	Port Type	adjustment range sec	DU	Article no.
Blade Terminal	12	5 x 6,3 mm	1 to 30	1	75614194
			30 to 900	1	75614001
Accessories			see	DU	
Relay Socket			Katalog04	5	50290266

Time Relay



With adjustable time relays with a switch-off delay, the precise delay time can be set within the selected time range using a potentiometer. There are five time ranges to choose from as standard. Function: operating voltage at terminal 15. Voltage at terminal 15 means that the relay is switched on immediately. If the voltage

is removed from terminal 15, the relay is switched off after the set time has elapsed. In a time relay with diodes, the relay does not consume any closed current after being switched off due to the diode circuitry. Applications: delayed switch-off for fans and lighting

Rated current: 10 A
Terminal/Clamp: Supply terminal 30
IP-Code: IP 54
WxHxD: 30 x 40 x 30 mm
Number of Poles: 5 terminal
Info: Switch-off delay

Plug type	Rated Voltage V	Port Type	adjustment range sec	DU	Article no.
Blade Terminal	12	5 x 6,3 mm	0 to 30	1	75614207
			30 to 900	1	75614005
Accessories			see	DU	
Relay Socket			Katalog04	5	50290266





Lighting

Assortment, plastic bulb	89
Bulb	85 - 89
Bulb plug	84
Cable Repair Set, high-beam headlamp bulb	84





Bulb plug

Bulb Type:
Info:

HB4
with cable



Number of Poles terminal	Socket Version	Cable Length mm	DU	Article no.
2	P22d PX22d	175	1	50390439
Accessories		Voltage V	see	DU
Bulb HB4		12	Katalog06	1
				89901129

Bulb plug

Bulb Type:
Info:

HB3
H12
with cable



Number of Poles terminal	Socket Version	Cable Length mm	DU	Article no.
2	P20d PZ20d PY20d	175	1	50390440
Accessories		Voltage V	see	DU
Bulb H12		12	Katalog06	1
Bulb HB3			Katalog06	1
				89901300
				89901128

Bulb plug

Bulb Type:

H8
H11
H27W/2
H16
H27W/1
with cable



Number of Poles terminal	Socket Version	Cable Length mm	DU	Article no.
2	PGJ19-1 PGJ19-2 PGJ13 PG13 PGJ19-3	175	1	50390441
Accessories		Voltage V	see	DU
Bulb H11		12	Katalog06	1
Bulb H27W/2			Katalog06	1
Bulb H8			Katalog06	1
				89901110
				89901302
				89901168

RepCon

- Cable Repair Set, high-beam headlamp bulb
- Cable Repair Set, main-beam headlamp bulb
- Cable Repair Set, fog light bulb

Bulb Type:

H9

Info:

with socket housing
with gaskets/seals
with pipe


Number of Poles terminal	Cable Length mm	Connector	DU	Article no.
2	500		1	51277310



D1S

Bulb

Xenon



Socket Version:

PK32d-2

Bulb Type:


D1S (gas discharge tube)

Voltage V	Rated Power W	DU	Article no.
85	35	1	89901320

D1R

Bulb

Xenon



Socket Version:

PK32d-3

Bulb Type:


D1R (gas discharge tube)

Voltage V	Rated Power W	DU	Article no.
85	35	1	89901321

D2S

Bulb

Xenon



Socket Version:

P32d-2

Bulb Type:


D2S (gas discharge tube)

Voltage V	Rated Power W	DU	Article no.
85	35	1	89901220

D2R

Bulb

Xenon



Socket Version:

P32d-3

Bulb Type:

D2R (gas discharge tube)

Voltage V	Rated Power W	DU	Article no.
85	35	1	89901221






D3S

Bulb

Xenon



Socket Version:

PK32d-5

Bulb Type:


D3S (Gas Discharge Lamp)

Voltage V	Rated Power W	DU	Article no.
42	35	1	89901313

D3R

Bulb

Xenon



Socket Version:

PK32d-6

Bulb Type:


D3R
Gas Discharge Lamp

Voltage V	Rated Power W	DU	Article no.
42	35	1	89901312

D4S

Bulb

Xenon



Socket Version:

P32d-5

Bulb Type:


D4S (Gas Discharge Lamp)

Voltage V	Rated Power W	DU	Article no.
42	35	1	89901314

D4R

Bulb

Xenon



Socket Version:

P32d-6


Bulb Type:

D4R
Gas Discharge Lamp

Voltage V	Rated Power W	DU	Article no.
42	35	1	89901319

P27/7W

Bulb



Socket Version:
Bulb Type:

WX2,5x16q
PY27/7W


Diameter:
Height:

26,5 mm
53 mm

Voltage V	Rated Power W	Bulb	DU	Article no.
12	27/7		10	89901324

H15

Bulb



Socket Version:

PGJ23t-1


Bulb Type:

H15

Voltage V	Rated Power W	DU	Article no.
12	55/15	1	89901335

P13W

Bulb



Socket Version:

PG18,5d-1


Bulb Type:

P13W

Voltage V	Rated Power W	DU	Article no.
12	13	1	89901332

PS19W

Bulb



Socket Version:

PG20-1

Bulb Type:

PS19W


Voltage V	Rated Power W	DU	Article no.
12	19	1	89901333





PSX24W

Bulb



Socket Version:

PG20-7

Bulb Type:


PSX24W

Voltage V	Rated Power W	Light Function	DU	Article no.
12	24	for fog lamp	1	89901334

HY21W

Bulb

Halogen



Socket Version:

BAW9s


Bulb Type:

HY21W

Voltage V	Rated Power W	Bulb	DU	Article no.
12	21		10	89901327

RY10W

Bulb



Socket Version:

BAU15s


Bulb Type:

RY10W

Voltage V	Rated Power W	Bulb	DU	Article no.
12	10		10	89901325

P27W

Bulb



Socket Version:
Bulb Type:

W2,5x16d
P27W

Diameter:
Height:

26,5 mm
53 mm

Voltage V	Rated Power W	DU	Article no.
12	27	10	89901310



4

P27/7W

Bulb



Socket Version:
Bulb Type:

W2,5x16q
P27/7W

Diameter:
Height:

26,5 mm
53 mm

Voltage V	Rated Power W	DU	Article no.
12	27/7	10	89901311

Assortment, plastic bulb

Material:

Plastic



Thanks to a range of plastic socket lamps, the most popular types are always available. This saves you valuable time during repair works.

Voltage V	Colour	Quantity	DU	Article no.	
12	● ○	60	1	89900206	
Content	Voltage V	Bulb Type	Socket Version	QU	Article no.
Plastic bulb	12	Socket Bulb	B8,3d	5	89901240
	12	Socket Bulb	B8,4d	5	89901284
	12	Socket Bulb	B8,5d	5	89901242
	12	Socket Bulb	B8,5d	5	89901244
	12	Socket Bulb	B8,5d	5	89901275
	12	Socket Bulb	BX8,4d	5	89901232
	12	Socket Bulb	BX8,4d	5	89901235
	12	Socket Bulb	BX8,4d	5	89901272
	12	Socket Bulb	BX8,4d	5	89901273
	12	Socket Bulb	BX8,4d	5	89901286
	12	Socket Bulb	BX8,5d	5	89901270
	12	Socket Bulb	BX8,5d	5	89901277

Assortment, plastic bulb

Material:

Plastic



Thanks to a range of plastic socket lamps, the most popular types are always available. This saves you valuable time during repair works.

Voltage V	Colour	Quantity	DU	Article no.	
12	● ○	90	1	89900207	
Content	Voltage V	Bulb Type	Socket Version	QU	Article no.
Plastic bulb	12	Socket Bulb	B8,3d	5	89901240
	12	Socket Bulb	B8,3d	5	89901282
	12	Socket Bulb	B8,4d	5	89901284
	12	Socket Bulb	B8,5d	5	89901242
	12	Socket Bulb	B8,5d	5	89901244
	12	Socket Bulb	B8,5d	5	89901275
	12	Socket Bulb	B8,7d	5	89901280
	12	Socket Bulb	BX8,4d	5	89901232
	12	Socket Bulb	BX8,4d	5	89901235
	12	Socket Bulb	BX8,4d	5	89901272
	12	Socket Bulb	BX8,4d	5	89901273
	12	Socket Bulb	BX8,5d	5	89901270
	12	Socket Bulb	BX8,5d	5	89901276
	12	Socket Bulb	BX8,5d	5	89901277
	12	Socket Bulb	BX8,5d	5	89901283
	12	Socket Bulb	MFHZ BG8-5,5d	5	89901279
	12	Socket Bulb	MFJF BG8,5-5,5d	5	89901278



ELPARTS



E-catalogues! Quick, easy, online




- realistic page-turning
- zoom, article search, thumbnail view, table of contents, bookmarks ...
- links and connection to online catalogue
- can be viewed on mobile devices




herthundbuss.com/en/catalogues

Main catalogues




Katalog04EN



Katalog06EN



Katalog08EN



Katalog13EN

ELPARTS | JAKOPARTS

 **HERTH+BUSS**

Your Herth+Buss partner

Herth+Buss Fahrzeugteile GmbH & Co. KG
Dieselstraße 2-4 | DE-63150 Heusenstamm

Herth+Buss France SAS
ZA Portes du Vercors, 270 Rue Col de La Chau
FR-26300 Châteauneuf-sur-Isère

Herth+Buss Belgium Sprl
Rue de Fisine 9 | BE-5590 Achêne

Herth+Buss UK Ltd.
Unit 1 Andyfreight Business Pk
Folkes Road, Lye | GB-DY9 8RB Stourbridge

Herth+Buss Iberica
C/A 44 Poligono de Areta
31620 Huarte Navarra | España



Brosch14EN | 06-2019

 **HERTH+BUSS**