

The SelectH₂ types

It's your choice!



	SelectH ₂	SelectH ₂	SelectH ₂ slim	SelectH ₂ mini
	95980002	95980024	95980025	95980019
Gauge	with illuminated LCD display, with battery state display, with LED display	with illuminated LCD display, with battery state display, with LED display	with illuminated LCD display, with battery state display, with LED display	with illuminated LCD display, with battery state display
Length gooseneck	320 mm	500 mm	500 mm	320 mm
Housing type	Aluminium housing	Aluminium housing	Aluminium housing	Synthetic material housing
Double sensors GG5 1000 / GGS 6000	broad band H ₂ -selective	broad band H ₂ -selective	broad band H ₂ -selective	broad band H ₂ -selective
WxHxD	52x178x35 mm	52x178x35 mm	52x178x28 mm	44x175x36 mm
With acoustic alarm	■	■	■	■
With integrated work light				■
With suction pump	■	■	■	
With extra slim sensor head			■	
Automatic zero-point calibration in fresh air	■	■	■	■
Automatic sensor check with error detection	■	■	■	■
Power supply				
Output voltage	12 V	12 V	12 V	9 V
Plug type	Round plug	Round plug	Round plug	Round plug
Diameter	3,5 mm	3,5 mm	3,5 mm	2,5 mm